



0603X474K160CT Information



For Reference Only

Part Number 0603X474K160CT

Manufacturer Walsin Technology Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.47UF 16V X5R 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0603X474K160CT Specifications

Manufacturer Part Number 0603X474K160CT Manufacturer Walsin Technology Corporation Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 0.47µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC
Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 0.47μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate -
Package Ceramic Capacitors Package 0603 (1608 Metric) Series - Capacitance 0.47 μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate -
Package0603 (1608 Metric)Series-Capacitance0.47μFTolerance $\pm 10\%$ Voltage - Rated16VTemperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-
Series-Capacitance $0.47μF$ Tolerance $±10%$ Voltage - Rated $16V$ Temperature Coefficient $X5R$ Operating Temperature $-55°C \sim 85°C$ Features-Ratings-ApplicationsGeneral PurposeFailure Rate-
Capacitance $0.47\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $16V$ Temperature CoefficientX5ROperating Temperature -55° C ~ 85° CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-
Tolerance $\pm 10\%$ Voltage - Rated $16V$ Temperature Coefficient $X5R$ Operating Temperature $-55^{\circ}C \sim 85^{\circ}C$ Features $-$ Ratings $-$ Applications $-$ Failure Rate $-$
Voltage - Rated Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Country Failure Rate 16V A5P A5P Country Country
Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate -
Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate -
Features Ratings Applications General Purpose
Ratings - Applications General Purpose Failure Rate -
Applications General Purpose Failure Rate -
Failure Rate -
Mounting Type Surface Mount, MLCC
Package / Case 0603 (1608 Metric)
Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)
Height - Seated (Max)
Thickness (Max) 0.037" (0.95mm)
Lead Spacing -
Lead Style -
Report error

0603X474K160CT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0603X474K160CT Payment Methods





















0603X474K160CT Shipping Methods













If you have any question about 0603X474K160CT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com