



0603Y0500562JXT Information



For Reference Only

Part Number 0603Y0500562JXT
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 5600PF 50V X7R 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0603Y0500562JXT Specifications

Manufacturer Part Number0603 Y0500562 JXTManufacturerKnowles SyferCategoryCapacitorsPackage0603 (1608 Metric)SeriesFlexiCap?Capacitance5600pFTolerance±5%Voltage - Rated50VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex Sensitive
Category Capacitors Ceramic Capacitors Package 0603 (1608 Metric) Series FlexiCap? Capacitance 5600pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Ratings -
Ceramic Capacitors Package 0603 (1608 Metric) Series FlexiCap? Capacitance 5600pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings -
Package0603 (1608 Metric)SeriesFlexiCap?Capacitance5600pFTolerance±5%Voltage - Rated50VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-
SeriesFlexiCap?Capacitance $5600pF$ Tolerance $\pm 5\%$ Voltage - Rated $50V$ Temperature Coefficient $X7R$ (2R1)Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesSoft Termination, High TemperatureRatings-
Capacitance 5600pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings -
Tolerance $\pm 5\%$ Voltage - Rated $50V$ Temperature Coefficient $X7R$ (2R1) Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Soft Termination, High Temperature Ratings -
Voltage - Rated50VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-
Temperature Coefficient X7R (2R1) Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Features Soft Termination, High Temperature Ratings -
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings -
Features Soft Termination, High Temperature Ratings -
Ratings -
Applications High Reliability, Boardflex Sensitive
Failure Rate -
Mounting Type Surface Mount, MLCC
Package / Case 0603 (1608 Metric)
Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)
Height - Seated (Max)
Thickness (Max) 0.031" (0.80mm)
Lead Spacing -
Lead Style -
Report errors

0603Y0500562JXT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0603Y0500562JXT Payment Methods



















0603Y0500562JXT Shipping Methods













If you have any question about 0603Y0500562JXT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com