



0603Y2000151JXT Information



For Reference Only

Part Number 0603Y2000151JXT
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 150PF 200V X7R 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0603Y2000151JXT Specifications

Manufacturer Part Number 0603Y2000151JXT Manufacturer Knowles Syfer Category Capacitors Package 0603 (1608 Metric) Series FlexiCap? Capacitance 150pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Spacing -		
Category Capacitors Package 0603 (1608 Metric) Series FlexiCap? Capacitance 150pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Manufacturer Part Number	0603Y2000151JXT
Package 0603 (1608 Metric) Series FlexiCap? Capacitance 150pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Manufacturer	Knowles Syfer
Package 0603 (1608 Metric) Series FlexiCap? Capacitance 150pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Category	Capacitors
SeriesFlexiCap?Capacitance150pFTolerance±5%Voltage - Rated200VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.031" (0.80mm)Lead Spacing-		Ceramic Capacitors
Capacitance 150pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Package	0603 (1608 Metric)
Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Series	FlexiCap?
Voltage - Rated Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Capacitance	150pF
Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Tolerance	±5%
Operating Temperature Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) 0.031" (0.80mm) Lead Spacing - Soft Termination, High Temperature Soft Temperature - Soft Temination, High Temperature - Soft Temination - Soft	Voltage - Rated	200V
Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Temperature Coefficient	X7R (2R1)
Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Features	Soft Termination, High Temperature
Failure Rate Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Applications	High Reliability, Boardflex Sensitive
Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - - - - - - - - - - - - -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.031" (0.80mm) Lead Spacing -	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.031" (0.80mm)
Lead Style -	Lead Spacing	-
Doub Style	Lead Style	-
Report errors		Report errors?

0603Y2000151JXT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0603Y2000151JXT Payment Methods



















0603Y2000151JXT Shipping Methods













If you have any question about 0603Y2000151JXT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com