




0603YD223MAT2A Information



For Reference Only

Part Number 0603YD223MAT2A Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.022UF 16V X5R 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0603YD223MAT2A Specifications

Manufacturer Part Number 0603YD223MAT2A Manufacturer AVX Corporation Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 0.022µF Tolerance ±20% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 0.022µF Tolerance ±20% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0603YD223MAT2A
Package O603 (1608 Metric) Series - Capacitance 0.022μF Tolerance ±20% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package 0603 (1608 Metric) Series - Capacitance 0.022μF Tolerance ±20% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 0.022μF Tolerance ±20% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.022μF Tolerance ±20% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Package	0603 (1608 Metric)
Tolerance ±20% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Capacitance	0.022μF
Temperature Coefficient Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style X5R A5R A5R A5R A5R - Coefficient A5R A5R - Coefficient A5R A5R - Coefficient A5R Coef	Tolerance	±20%
Operating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.90mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Temperature Coefficient	X5R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Features	-
Failure Rate Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.81mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.90mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0603YD223MAT2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0603YD223MAT2A Payment Methods



















0603YD223MAT2A Shipping Methods













If you have any question about 0603YD223MAT2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com