



0603ZC123KAT4A Information



For Reference Only

Part Number 0603ZC123KAT4A
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 0.012UF 10V X7R 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0603ZC123KAT4A Specifications

Manufacturer Part Number 0603ZC123KAT4A Manufacturer AVX Corporation Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 0.012µF Tolerance ±10% Voltage - Rated 10V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 0.012µF Tolerance ±10% Voltage - Rated 10V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0603ZC123KAT4A
Package 0603 (1608 Metric) Series - Capacitance 0.012μF Tolerance ±10% Voltage - Rated 10V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package 0603 (1608 Metric) Series - Capacitance 0.012μF Tolerance ±10% Voltage - Rated 10V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 0.012μF Tolerance ±10% Voltage - Rated 10V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.012μF Tolerance ±10% Voltage - Rated 10V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Package	0603 (1608 Metric)
Tolerance ±10% Voltage - Rated 10V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style	Capacitance	0.012μF
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style - X7R A7R A7R A7R A7R A7R A7R A7R	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.90mm)Lead Spacing-Lead Style-	Voltage - Rated	10V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.81mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.90mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0603ZC123KAT4A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0603ZC123KAT4A Payment Methods



















0603ZC123KAT4A Shipping Methods













If you have any question about 0603ZC123KAT4A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com