



### 0603ZD475KAT2A Information



For Reference Only

Part Number 0603ZD475KAT2A
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

**Description** CAP CER 4.7UF 10V X5R 0603

**Package** 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 0603ZD475KAT2A Specifications

Manufacturer Part Number         0603ZD475KAT2A           Manufacturer         AVX Corporation           Category         Capacitors           Package         0603 (1608 Metric)           Series         -           Capacitance         4.7µF           Tolerance         ±10%           Voltage - Rated         10V           Temperature Coefficient         X5R           Operating Temperature         -55°C ~ 85°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.032" W (1.60mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.90mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         0603 (1608 Metric)           Series         -           Capacitance         4.7µF           Tolerance         ±10%           Voltage - Rated         10V           Temperature Coefficient         X5R           Operating Temperature         -55°C ~ 85°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.032" W (1.60mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.90mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	0603ZD475KAT2A
Package         0603 (1608 Metric)           Series         -           Capacitance         4.7μF           Tolerance         ±10%           Voltage - Rated         10V           Temperature Coefficient         X5R           Operating Temperature         -55°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.032" W (1.60mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.90mm)           Lead Spacing         -           Lead Style         -	Manufacturer	AVX Corporation
Package         0603 (1608 Metric)           Series         -           Capacitance         4.7μF           Tolerance         ±10%           Voltage - Rated         10V           Temperature Coefficient         X5R           Operating Temperature         -55°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.032" W (1.60mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.90mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         -           Capacitance         4.7μF           Tolerance         ±10%           Voltage - Rated         10V           Temperature Coefficient         X5R           Operating Temperature         -55°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.032" W (1.60mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.90mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance       4.7µF         Tolerance       ±10%         Voltage - Rated       10V         Temperature Coefficient       X5R         Operating Temperature       -55°C ~ 85°C         Features       -         Ratings       -         Applications       General Purpose         Failure Rate       -         Mounting Type       Surface Mount, MLCC         Package / Case       0603 (1608 Metric)         Size / Dimension       0.063" L x 0.032" W (1.60mm x 0.81mm)         Height - Seated (Max)       -         Thickness (Max)       0.035" (0.90mm)         Lead Spacing       -         Lead Style       -	Package	0603 (1608 Metric)
Tolerance         ±10%           Voltage - Rated         10V           Temperature Coefficient         X5R           Operating Temperature         -55°C ~ 85°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.032" W (1.60mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.90mm)           Lead Spacing         -           Lead Style         -	Series	-
Voltage - Rated10VTemperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.90mm)Lead Spacing-Lead Style-	Capacitance	4.7μF
Temperature Coefficient  NSR  Operating Temperature  -55°C ~ 85°C  Features  - Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  0603 (1608 Metric)  Size / Dimension  0.063" L x 0.032" W (1.60mm x 0.81mm)  Height - Seated (Max)  Thickness (Max)  0.035" (0.90mm)  Lead Spacing  - Lead Style  -  Since / Sinc	Tolerance	±10%
Operating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.90mm)Lead Spacing-Lead Style-	Voltage - Rated	10V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Temperature Coefficient	X5R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Features	-
Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.032" W (1.60mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.90mm)           Lead Spacing         -           Lead Style         -	Ratings	-
Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.032" W (1.60mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.90mm)           Lead Spacing         -           Lead Style         -	Applications	General Purpose
Package / Case       0603 (1608 Metric)         Size / Dimension       0.063" L x 0.032" W (1.60mm x 0.81mm)         Height - Seated (Max)       -         Thickness (Max)       0.035" (0.90mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.063" L x 0.032" W (1.60mm x 0.81mm)         Height - Seated (Max)       -         Thickness (Max)       0.035" (0.90mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.035" (0.90mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.81mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.90mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### 0603ZD475KAT2A Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 0603ZD475KAT2A Payment Methods



















## 0603ZD475KAT2A Shipping Methods













If you have any question about 0603ZD475KAT2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com