



06125C223KAT2A Information



For Reference Only

Part Number 06125C223KAT2A Manufacturer AVX Corporation Category

Capacitors

Ceramic Capacitors **Description** CAP CER 0.022UF 50V X7R 0612

Package 0612 (1632 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









06125C223KAT2A Specifications

Manufacturer Part Number $06125C223KAT2A$ ManufacturerAVX CorporationCategoryCapacitorsPackage 0612 (1632 Metric)Series-Capacitance $0.022\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $50V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesLow ESL (Reverse Geometry)	
Category Capacitors Ceramic Capacitors Package 0612 (1632 Metric) Series - Capacitance 0.022 μ F Tolerance $\pm 10\%$ Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C	
Ceramic CapacitorsPackage $0612 (1632 \text{ Metric})$ Series-Capacitance $0.022 \mu F$ Tolerance $\pm 10\%$ Voltage - Rated $50V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Package $0612 (1632 \text{ Metric})$ Series-Capacitance $0.022\mu\text{F}$ Tolerance $\pm 10\%$ Voltage - Rated 50V Temperature CoefficientX7ROperating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Series-Capacitance $0.022\mu F$ Tolerance $±10\%$ Voltage - Rated $50V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
Capacitance $0.022\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $50V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
Tolerance $\pm 10\%$ Voltage - Rated $50V$ Temperature Coefficient X7R Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C	
Temperature Coefficient X7R Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Eastures Low ESI (Payarsa Coometry)	
readules Low ESL (Reverse Geometry)	
Ratings -	
Applications Bypass, Decoupling	
Failure Rate -	
Mounting Type Surface Mount, MLCC	
Package / Case 0612 (1632 Metric)	
Size / Dimension 0.063" L x 0.126" W (1.60mm x 3.20mm)	
Height - Seated (Max)	
Thickness (Max) 0.037" (0.94mm)	
Lead Spacing -	
Lead Style -	
Report error	rs?

06125C223KAT2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

06125C223KAT2A Payment Methods



















06125C223KAT2A Shipping Methods













If you have any question about 06125C223KAT2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com