

# 067406.3MXEP Information



For Reference Only

Part Number 067406.3MXEP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

**Description** FUSE CERAMIC 6.3A 250VAC AXIAL

Package Cartridge, Non-Standard (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **067406.3MXEP Specifications**

Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Fuses  Package  Package  Cartridge, Non-Standard (Axial)  Series  Fuse Type  Cartridge, Ceramic  Current Rating  Current Rating  Current Rating - AC  Voltage Rating - DC  Response Time  Package / Case  Package / Case  Cartridge, Non-Standard (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting 12t  Approvals  Concepting Temperature	•	
Category  Circuit Protection Fuses  Package  Cartridge, Non-Standard (Axial)  Series  674  Fuse Type  Cartridge, Ceramic  Current Rating  6.3A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Package / Case  Cartridge, Non-Standard (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  Circuit Protection  Fuses  Cartridge, Non-Standard (Axial)  Through Hole  SoA  Melting I2t  CSA, UL	Manufacturer Part Number	067406.3MXEP
Fuses Package Cartridge, Non-Standard (Axial) Series 674 Fuse Type Cartridge, Ceramic Current Rating 6.3A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 19.2 Approvals CSA, UL	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard (Axial)  Series 674  Fuse Type Cartridge, Ceramic  Current Rating 6.3A  Voltage Rating - AC 250V  Voltage Rating - DC -  Response Time Fast  Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 50A  Melting 12t 19.2  Approvals Cartridge, Non-Standard (Axial)	Category	Circuit Protection
Series 674 Fuse Type Cartridge, Ceramic Current Rating 6.3A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 19.2 Approvals CSA, UL		Fuses
Fuse Type Cartridge, Ceramic  Current Rating 6.3A  Voltage Rating - AC 250V  Voltage Rating - DC -  Response Time Fast  Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 50A  Melting I2t 19.2  Approvals CSA, UL	Package	Cartridge, Non-Standard (Axial)
Current Rating  Voltage Rating - AC  250V  Voltage Rating - DC  Response Time  Fast  Package / Case  Cartridge, Non-Standard (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  6.3A  250V  Cartridge, Non-Standard  (Axial)  Through Hole  50A  CSA, UL	Series	674
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Package / Case  Cartridge, Non-Standard (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CSA, UL	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC  Response Time Fast  Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t Approvals CSA, UL	Current Rating	6.3A
Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 19.2 Approvals CSA, UL	Voltage Rating - AC	250V
Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 50A  Melting I2t 19.2  Approvals CSA, UL	Voltage Rating - DC	-
Mounting Type  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  Through Hole  50A  CSA, UL	Response Time	Fast
Breaking Capacity @ Rated Voltage 50A  Melting I2t 19.2  Approvals CSA, UL	Package / Case	Cartridge, Non-Standard (Axial)
Melting I2t 19.2 Approvals CSA, UL	Mounting Type	Through Hole
Approvals CSA, UL	Breaking Capacity @ Rated Voltage	50A
	Melting I2t	19.2
Operating Temperature	Approvals	CSA, UL
Operating reinperature	Operating Temperature	-
Color -	Color	-
Size / Dimension 0.154" Dia x 0.433" L (3.90mm x 11.00mm)	Size / Dimension	0.154" Dia x 0.433" L (3.90mm x 11.00mm)
Report errors?		Report errors?

#### 067406.3MXEP Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 067406.3MXEP Payment Methods



















### 067406.3MXEP Shipping Methods













If you have any question about 067406.3MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com