



## 0676005.MXEP Information



For Reference Only

Part Number 0676005.MXEP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

**Description** FUSE CERAMIC 5A 250VAC AXIAL

Package Cartridge, Non-Standard (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 0676005.MXEP Specifications

Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Fuses  Package  Cartridge, Non-Standard (Axial)  Series  Fuse Type  Cartridge, Ceramic  Current Rating  5A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Package / Case  Cartridge, Non-Standard (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  Operating Temperature  Color	•	
Category  Circuit Protection  Fuses  Package  Cartridge, Non-Standard (Axial)  Series  676  Fuse Type  Cartridge, Ceramic  Current Rating  5A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Package / Case  Cartridge, Non-Standard (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  Operating Temperature  -  Cartridge, Non-Standard (Axial)  CCC, CSA, UL, VDE  Operating Temperature	Manufacturer Part Number	0676005.MXEP
Fuses Package Cartridge, Non-Standard (Axial) Series 676 Fuse Type Cartridge, Ceramic Current Rating 5A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 20.4 Approvals CCC, CSA, UL, VDE Operating Temperature -	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard (Axial)  Series 676  Fuse Type Cartridge, Ceramic  Current Rating 5A  Voltage Rating - AC 250V  Voltage Rating - DC -  Response Time Fast  Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 50A  Melting I2t 20.4  Approvals CCC, CSA, UL, VDE  Operating Temperature -	Category	Circuit Protection
Series 676 Fuse Type Cartridge, Ceramic Current Rating 5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 20.4 Approvals CCC, CSA, UL, VDE Operating Temperature -		Fuses
Fuse Type Cartridge, Ceramic  Current Rating 5A  Voltage Rating - AC 250V  Voltage Rating - DC -  Response Time Fast  Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 50A  Melting I2t 20.4  Approvals CCC, CSA, UL, VDE  Operating Temperature -	Package	Cartridge, Non-Standard (Axial)
Current Rating 5A  Voltage Rating - AC 250V  Voltage Rating - DC -  Response Time Fast  Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 50A  Melting I2t 20.4  Approvals CCC, CSA, UL, VDE  Operating Temperature -	Series	676
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Package / Case  Cartridge, Non-Standard (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CCC, CSA, UL, VDE  Operating Temperature	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC  Response Time Fast  Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t Approvals CCC, CSA, UL, VDE  Operating Temperature -	Current Rating	5A
Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 20.4 Approvals CCC, CSA, UL, VDE Operating Temperature -	Voltage Rating - AC	250V
Package / Case Cartridge, Non-Standard (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 50A  Melting I2t 20.4  Approvals CCC, CSA, UL, VDE  Operating Temperature -	Voltage Rating - DC	-
Mounting Type  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CCC, CSA, UL, VDE  Operating Temperature  Through Hole  50A  CCC, CSA, UL, VDE	Response Time	Fast
Breaking Capacity @ Rated Voltage 50A  Melting I2t 20.4  Approvals CCC, CSA, UL, VDE  Operating Temperature -	Package / Case	Cartridge, Non-Standard (Axial)
Melting I2t 20.4  Approvals CCC, CSA, UL, VDE  Operating Temperature -	Mounting Type	Through Hole
Approvals CCC, CSA, UL, VDE Operating Temperature -	Breaking Capacity @ Rated Voltage	50A
Operating Temperature -	Melting I2t	20.4
	Approvals	CCC, CSA, UL, VDE
Color -	Operating Temperature	-
Color	Color	-
Size / Dimension 0.154" Dia x 0.433" L (3.90mm x 11.00mm)	Size / Dimension	0.154" Dia x 0.433" L (3.90mm x 11.00mm)
Report errors?		Report errors?

#### 0676005.MXEP Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 0676005.MXEP Payment Methods

































If you have any question about 0676005.MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com