

## 0678L9200-02

#### 0678L9200-02 Information



Number	0678L9200-02	
ufacturer	Bel Fuse Inc.	
gory	Circuit Protection Fuses	
ription	FUSE BOARD MNT 20A 250VAC 72VDC	
age	2-SMD, Square End Block	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

**Certified Quality** 

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 0678L9200-02 Specifications

Manufacturer Part Number0678L9200-02ManufacturerBel Fuse Inc.CategoryCircuit ProtectionFusesPackage2-SMD, Square End BlockSeries0678LFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating20AVoltage Rating - AC250VVoltage Rating - DC72VResponse TimeMediumPackage / Case2-SMD, Square End BlockMounting Type2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage100A AC, 130A DCMelting I2t270Approvalscurrent Score Alsone ConstraintsOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)			
CategoryCircuit ProtectionFusesPackage2-SMD, Square End BlockSeries0678LFuse TypeBoard Mount (Catridge Style Excluded)Current Rating20AVoltage Rating - AC250VVoltage Rating - DC72VResponse TimeMediumPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage100A AC, 130A DCApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.386" L x 0.120" W x 0.125" H (0.80mm x 3.05mm x 3.18mm)	Manufacturer Part Number	0678L9200-02	
FusesPackage2-SMD, Square End BlockSeries0678LFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating20AVoltage Rating - AC250VVoltage Rating - DC72VResponse TimeMediumPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage100A AC, 130A DCMelting 12t270ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.386" L x 0.120" W x 0.125" H (9.80mm x 3.18mm)	Manufacturer	Bel Fuse Inc.	
Package SMD, Square End Block   Series 0678L   Fuse Type Board Mount (Cartridge Style Excluded)   Fuse Type 00A   Current Rating 20A   Voltage Rating - AC 250V   Voltage Rating - DC 72V   Response Time Medium   Package / Case Surface Mount   Mounting Type Surface Mount   Package / Case 100A AC, 130A DC   Melting I2t 270   Approvals cURus   Operating Temperature 55°C ~ 125°C   Color -   Stez / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.18mm)	Category	Circuit Protection	
Series0678LFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating20AVoltage Rating - AC250VVoltage Rating - DC72VResponse TimeMediumPackage / Case2-SMD, Square End BlockMounting Type100A AC, 130A DCBreaking Capacity @ Rated Voltage100A AC, 130A DCMelting I2t270ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.386° L x 0.120° W x 0.125° H (0.80mm x 3.05mm x 3.18mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Fuse Type0ACurrent Rating20AVoltage Rating - AC250VVoltage Rating - DC72VResponse TimeMediumPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage100A AC, 130A DCMelting I2t270ApprovalscURusOperating Temperature-55°C ~ 125°CColor.Size / Dimension0.386" L x 0.120" W x 0.125" H (9.80mm x 3.18mm)	Package	2-SMD, Square End Block	
Current Rating 20A   Voltage Rating - AC 250V   Voltage Rating - DC 72V   Response Time Medium   Package / Case Surface Mount   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 100A AC, 130A DC   Melting I2t 270   Approvals cURus   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Series	0678L	
Voltage Rating - AC250VVoltage Rating - DC72VResponse TimeMediumPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage100A AC, 130A DCMelting I2t270ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC72VResponse TimeMediumPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage100A AC, 130A DCMelting I2t270ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.386" L x 0.120" W x 0.125" H (9.80m x 3.05mm x 3.18mm)	Current Rating	20A	
Response Time Medium   Package / Case 2-SMD, Square End Block   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 100A AC, 130A DC   Melting I2t 270   Approvals cURus   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Voltage Rating - AC	250V	
Package / Case 2-SMD, Square End Block   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 100A AC, 130A DC   Melting I2t 270   Approvals cURus   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Voltage Rating - DC	72V	
Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 100A AC, 130A DC   Melting I2t 270   Approvals cURus   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Response Time	Medium	
Breaking Capacity @ Rated Voltage100A AC, 130A DCMelting I2t270ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Package / Case	2-SMD, Square End Block	
Melting I2t 270   Approvals cURus   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Mounting Type	Surface Mount	
Approvals cURus   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Breaking Capacity @ Rated Voltage	100A AC, 130A DC	
Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Melting I2t	270	
Color -   Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Approvals	cURus	
Size / Dimension 0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.386" L x 0.120" W x 0.125" H (9.80mm x 3.05mm x 3.18mm)	
			Report errors?

#### 0678L9200-02 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 0678L9200-02 Payment Methods



#### 0678L9200-02 Shipping Methods



If you have any question about 0678L9200-02, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com