

### 0679H0630-05

#### 0679H0630-05 Information





## FUSE BRD MNT 630MA 350VAC 72VDC For the pricing/inventory/lead time, please contact Website: https://www.heisener.com E-mail: salesdept@heisener.com



**Request a Quote** 

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### 0679H0630-05 Specifications

Manufacturer Part Number0679H0630-05ManufacturerBel Fuse Inc.CategoryCircuit ProtectionFusesPackage2410 (6125 Metric)Series0679HFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating630mAVoltage Rating - AC350VVoltage Rating - DC72VResponse TimeFastPackage / Case2410 (6125 Metric)Mounting TypeSon ACNoting TypeSon ACMounting TypeSon ACMounting TypeSon ACApprovalsCircues CaseApprovalsCircues CaseColor-55°C ~ 125°CColor-20°CSize / Dimension0.40°L x 0.100°W x 0.110°H (6.10mm x 2.54mm x 2.79mm)			
Category   Circuit Protection     Fuses   Fuses     Package   2410 (6125 Metric)     Series   0679H     Fuse Type   Board Mount (Catrridge Style Excluded)     Current Rating   630mA     Voltage Rating - AC   350V     Voltage Rating - DC   72V     Response Time   Fast     Package / Case   2410 (6125 Metric)     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A AC, 100A DC     Melting I2t   0.15     Approvals   cURus     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240° "L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Manufacturer Part Number	0679H0630-05	
FusesPackage2410 (6125 Metric)Series0679HFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating630mAVoltage Rating - AC350VVoltage Rating - DC72VResponse TimeFastPackage / Case2410 (6125 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50A AC, 100A DCMetting I2t0.15ApproalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240° L x 0.100° W x 0.110° H (6.10mm x 2.54mm x 2.79mm)	Manufacturer	Bel Fuse Inc.	
Package   2410 (6125 Metric)     Series   0679H     Fuse Type   Board Mount (Cartridge Style Excluded)     Fuse Type   630mA     Current Rating   630mA     Voltage Rating - AC   350V     Voltage Rating - DC   72V     Response Time   Fast     Package / Case   2410 (6125 Metric)     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   Surface Mount     Approvals   0.15     Approvals   cURus     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dinension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Category	Circuit Protection	
Series   0679H     Fuse Type   Board Mount (Cartridge Style Excluded)     Current Rating   630mA     Voltage Rating - AC   350V     Voltage Rating - DC   72V     Response Time   Fast     Package / Case   2410 (6125 Metric)     Mounting Type   Sof AC, 100A DC     Preaking Capacity @ Rated Voltage   50A AC, 100A DC     Metring I2t   0.15     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240″ L x 0.100″ W x 0.110″ H (6.10mm x 2.54mm x 2.79mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Fuse Type630mACurrent Rating630mAVoltage Rating - AC350VVoltage Rating - DC72VResponse TimeFastPackage / Case2410 (6125 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50A AC, 100A DCMelting I2t0.15ApprovalscURusOperating Temperature-55°C ~ 125°CColor.Size / Dimension0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Package	2410 (6125 Metric)	
Current Rating   630mA     Voltage Rating - AC   350V     Voltage Rating - DC   72V     Response Time   Fast     Package / Case   2410 (6125 Metric)     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A AC, 100A DC     Melting I2t   0.15     Approvals   cURus     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Series	0679H	
Voltage Rating - AC350VVoltage Rating - DC72VResponse TimeFastPackage / Case2410 (6125 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50A AC, 100A DCMelting I2t0.15ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC72VResponse TimeFastPackage / Case2410 (6125 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50A AC, 100A DCMelting I2t0.15ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Current Rating	630mA	
Response Time   Fast     Package / Case   2410 (6125 Metric)     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A AC, 100A DC     Melting I2t   0.15     Approvals   cURus     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Voltage Rating - AC	350V	
Package / Case 2410 (6125 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A AC, 100A DC   Melting I2t 0.15   Approvals cURus   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Voltage Rating - DC	72V	
Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A AC, 100A DC     Melting I2t   0.15     Approvals   cURus     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Response Time	Fast	
Breaking Capacity @ Rated Voltage   50A AC, 100A DC     Melting I2t   0.15     Approvals   cURus     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Package / Case	2410 (6125 Metric)	
Melting I2t   0.15     Approvals   cURus     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Mounting Type	Surface Mount	
Approvals   cURus     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Breaking Capacity @ Rated Voltage	50A AC, 100A DC	
Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Melting I2t	0.15	
Color   -     Size / Dimension   0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Approvals	cURus	
Size / Dimension 0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.240" L x 0.100" W x 0.110" H (6.10mm x 2.54mm x 2.79mm)	
			Report errors?

#### 0679H0630-05 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 0679H0630-05 Payment Methods





If you have any question about 0679H0630-05, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com