

0697H0630-02

Request a Quote

0697H0630-02 Information

	Part Number	0697H0630-02
	Manufacturer	Bel Fuse Inc.
www.treiseger.com	Category	Circuit Protection Fuses
	Description	FUSE BRD MNT 630MA 350VAC 100VDC
	Package	Radial, Box
		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0697H0630-02 Specifications

Manufacturer Bel Fuse Inc. Category Circuit Protection Fuses Fuses Package Radial, Box Series 0697H Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 630mA Voltage Rating - AC 350V Voltage Rating - DC 100V Response Time Slow Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 65A DC Melting I2t 1.5 Approvals curRus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)			
CategoryCircuit ProtectionFusesPackageRadial, BoxSeries0697HFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating630mAVoltage Rating - AC350VVoltage Rating - DC100VResponse TimeSlowPackage / CaseRadial, BoxMounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 65A DCApprovalscURusOperating Temperature.55°C ~ 125°CColor.Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Manufacturer Part Number	0697H0630-02	
FusesPackageRadial, BoxSeries0697HFuse TypeBoard Mount (Cartridge Style Excluded)Fuse Type630mACurrent Rating630mAVoltage Rating - AC350VVoltage Rating - DC100VResponse TimeSlowPackage / CaseRadial, BoxMounting Type100A AC, 65A DCBreaking Capacity @ Rated Voltage100A AC, 65A DCMelting I2t1.5ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Manufacturer	Bel Fuse Inc.	
PackageRadial, BoxSeries6697HFuse TypeBoard Mount (Cartridge Style Excluded)Fuse Type630mACurrent Rating630mAVoltage Rating - AC350VVoltage Rating - DC100VResponse TimeSlowPackage / CaseRadial, BoxMounting Type100A AC, 65A DCBreaking Capacity @ Rated Voltage1.5ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Category	Circuit Protection	
Series 0697H Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 630mA Voltage Rating - AC 350V Voltage Rating - DC 100V Response Time Slow Nounting Type Radial, Box Mounting Type 100A AC, 65A DC Breaking Capacity @ Rated Voltage 100A AC, 65A DC Melting I2t 1.5 Approvals cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating630mAVoltage Rating - AC350VVoltage Rating - DC100VResponse TimeSlowPackage / CaseRadial, BoxMounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 65A DCMelting I2t1.5ApprovalscURusOperating Temperature-55°C ~ 125°CColor.Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Package	Radial, Box	
Current Rating 630mA Voltage Rating - AC 350V Voltage Rating - DC 100V Response Time Slow Package / Case Radial, Box Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 65A DC Melting I2t 1.5 Approvals cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Series	0697H	
Voltage Rating - AC350VVoltage Rating - DC100VResponse TimeSlowPackage / CaseRadial, BoxMounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 65A DCMelting I2t1.5ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC100VResponse TimeSlowPackage / CaseRadial, BoxMounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 65A DCMelting I2t1.5ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Current Rating	630mA	
Response TimeSlowPackage / CaseRadial, BoxMounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 65A DCMelting I2t1.5ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Voltage Rating - AC	350V	
Package / CaseRadial, BoxMounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 65A DCMelting I2t1.5ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Voltage Rating - DC	100V	
Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 65A DCMelting I2t1.5ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Response Time	Slow	
Breaking Capacity @ Rated Voltage 100A AC, 65A DC Melting I2t 1.5 Approvals cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Package / Case	Radial, Box	
Melting I2t 1.5 Approvals cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Mounting Type	Through Hole	
ApprovalscURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Breaking Capacity @ Rated Voltage	100A AC, 65A DC	
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Melting I2t	1.5	
Color - Size / Dimension 0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Approvals	cURus	
Size / Dimension 0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.329" L x 0.157" W x 0.307" H (8.35mm x 4.00mm x 7.80mm)	
*			Report errors?

0697H0630-02 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0697H0630-02 Payment Methods



0697H0630-02 Shipping Methods



If you have any question about 0697H0630-02, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com