

### 0708140 Information

Heisener.com

Part Number 0708140

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Panel Mount

**Description** TERM BLK HDR 5POS SCREW MNT GRN

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 0708140 Specifications

Manufacturer Part Number         0708140           Manufacturer         Phoenix Contact           Category         Connectors, Interconnects           Terminal Blocks - Panel Mount         Terminal Blocks - Panel Mount           Package         -           Series         COMBICON DFK-MSTB           Front Panel Wire Connection         Header, Male Pins           Rear Panel Wire Connection         Wire Wrap Terminals           Width         1.772" (45.00mm)           Panel Thickness         0.020 ~ 0.158" (0.5 ~ 4.0mm)           Positions Per Level         5           Panel Mount Type         Screw Mount - Front Flange           Pitch         0.197" (5.00mm)           Voltage - UL         300V           Current - UL         10A           Wire Gauge         -           Color         Green           Features         Lock Opening           Number of Levels         1	•	
Category Connectors, Interconnects Terminal Blocks - Panel Mount  Package - Series COMBICON DFK-MSTB Front Panel Wire Connection Header, Male Pins Wire Wrap Terminals Width 1.772" (45.00mm) Panel Thickness 0.020 ~ 0.158" (0.5 ~ 4.0mm) Positions Per Level 5 Panel Mount Type Screw Mount - Front Flange Pitch 0.197" (5.00mm)  Voltage - UL 0.197" (5.00mm)  Voltage - UL 10A Wire Gauge Color Green Features Lock Opening Number of Levels	Manufacturer Part Number	0708140
Package         -           Series         COMBICON DFK-MSTB           Front Panel Wire Connection         Header, Male Pins           Rear Panel Wire Connection         Wire Wrap Terminals           Width         1.772" (45.00mm)           Panel Thickness         0.020 ~ 0.158" (0.5 ~ 4.0mm)           Positions Per Level         5           Panel Mount Type         Screw Mount - Front Flange           Pitch         0.197" (5.00mm)           Voltage - UL         300V           Current - UL         10A           Wire Gauge         -           Color         Green           Features         Lock Opening           Number of Levels         1	Manufacturer	Phoenix Contact
Package - COMBICON DFK-MSTB Front Panel Wire Connection Header, Male Pins Rear Panel Wire Connection Wire Wrap Terminals Width 1.772" (45.00mm) Panel Thickness 0.020 ~ 0.158" (0.5 ~ 4.0mm) Positions Per Level 5 Panel Mount Type Screw Mount - Front Flange Pitch 0.197" (5.00mm) Voltage - UL 300V Current - UL 10A Wire Gauge - Color Green Features Lock Opening Number of Levels 1	Category	Connectors, Interconnects
Series COMBICON DFK-MSTB Front Panel Wire Connection Header, Male Pins Rear Panel Wire Connection Wire Wrap Terminals Width 1.772" (45.00mm) Panel Thickness 0.020 ~ 0.158" (0.5 ~ 4.0mm) Positions Per Level 5 Panel Mount Type Screw Mount - Front Flange Pitch 0.197" (5.00mm) Voltage - UL 300V Current - UL 10A Wire Gauge - Color Green Features Lock Opening Number of Levels 1		Terminal Blocks - Panel Mount
Front Panel Wire Connection  Rear Panel Wire Connection  Wire Wrap Terminals  1.772" (45.00mm)  Panel Thickness  0.020 ~ 0.158" (0.5 ~ 4.0mm)  Positions Per Level  5  Panel Mount Type  Screw Mount - Front Flange  Pitch  0.197" (5.00mm)  Voltage - UL  300V  Current - UL  10A  Wire Gauge  Color  Green  Features  Number of Levels  1	Package	-
Rear Panel Wire ConnectionWire Wrap TerminalsWidth1.772" (45.00mm)Panel Thickness0.020 ~ 0.158" (0.5 ~ 4.0mm)Positions Per Level5Panel Mount TypeScrew Mount - Front FlangePitch0.197" (5.00mm)Voltage - UL300VCurrent - UL10AWire Gauge-ColorGreenFeaturesLock OpeningNumber of Levels1	Series	COMBICON DFK-MSTB
Width       1.772" (45.00mm)         Panel Thickness       0.020 ~ 0.158" (0.5 ~ 4.0mm)         Positions Per Level       5         Panel Mount Type       Screw Mount - Front Flange         Pitch       0.197" (5.00mm)         Voltage - UL       300V         Current - UL       10A         Wire Gauge       -         Color       Green         Features       Lock Opening         Number of Levels       1	Front Panel Wire Connection	Header, Male Pins
Panel Thickness  O.020 ~ 0.158" (0.5 ~ 4.0mm)  Positions Per Level  5  Panel Mount Type  Screw Mount - Front Flange  Pitch  O.197" (5.00mm)  Voltage - UL  300V  Current - UL  10A  Wire Gauge  Color  Green  Features  Lock Opening  Number of Levels	Rear Panel Wire Connection	Wire Wrap Terminals
Positions Per Level 5 Panel Mount Type Screw Mount - Front Flange Pitch 0.197" (5.00mm)  Voltage - UL 300V  Current - UL 10A  Wire Gauge - Green  Features Lock Opening  Number of Levels 1	Width	1.772" (45.00mm)
Panel Mount Type  Pitch  0.197" (5.00mm)  Voltage - UL  300V  Current - UL  10A  Wire Gauge  -  Color  Features  Number of Levels  Screw Mount - Front Flange  0.197" (5.00mm)  300V  Tourent - UL  10A  Lock Opening  1	Panel Thickness	0.020 ~ 0.158" (0.5 ~ 4.0mm)
Pitch         0.197" (5.00mm)           Voltage - UL         300V           Current - UL         10A           Wire Gauge         -           Color         Green           Features         Lock Opening           Number of Levels         1	Positions Per Level	5
Voltage - UL         300V           Current - UL         10A           Wire Gauge         -           Color         Green           Features         Lock Opening           Number of Levels         1	Panel Mount Type	Screw Mount - Front Flange
Current - UL         10A           Wire Gauge         -           Color         Green           Features         Lock Opening           Number of Levels         1	Pitch	0.197" (5.00mm)
Wire Gauge - Color Green Features Lock Opening Number of Levels 1	Voltage - UL	300V
Color Green Features Lock Opening Number of Levels 1	Current - UL	10A
Features Lock Opening Number of Levels 1	Wire Gauge	-
Number of Levels 1	Color	Green
	Features	Lock Opening
D ( 0	Number of Levels	1
Report errors?		Report errors?

### 0708140 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0708140 Payment Methods





















# 0708140 Shipping Methods













If you have any question about 0708140, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com