

0719790208

uest a Quote

0719790208 Information

		0710700200
	Part Number	0/19/90208
	Manufacturer	Molex, LLC
Heisener.com	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets
	Description	CONN RCPT R/A DL SMD GOLD 16POS
	Package	-
For Reference Only		For the pricing/inventory/lead time, please contact us
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0719790208 Specifications

Manufacturer Part Number0719790208ManufacturerMolex, LLCCategoryConnectors, InterconnectsPackage-Package-SeriesCofrid? 71979Connector TypeReceptacles, Female SocketsContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions16Number of Positions Loaded1.00° (2.54mm)Number of Rows2Row Spacing - MatingSolderYourgeSurface Mount, Right AngleTerminationSolderStater TypeSolderContact Finish - MatingGoldContact Finish - MatingSolderState TypeSolderState TypeSolderState TypeSolderStation Legistions - MatingSolderContact Finish - MatingSolderContact Length -		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCofrid? 71979Connector TypeReceptacleContact TypeBeard to Board to CableStyleBoard to Board or CableNumber of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - MatingSolderMounting TypeSolderFermiationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish Thickness - MatingJiji (0.38µm)Solator Finish Thickness - MatingJisi (0.67mm)Solator Finish Thickness - MatingJisi (0.67mm)Contact Finish Thickness - MatingJisi (0.67mm)Solator Finish Thickness - MatingJisi (0.58mm)Solator Finish Thickness - MatingJisi (0.38µm)Solator Finish Thickness - MatingJisi (0.58mm)Solator Finish Thickness - MatingJisi (0.58mm)Solato	Manufacturer Part Number	0719790208
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesC-Grid? 71979Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions16Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSurface Mount, Right AngleYenniationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266° (6.76mm)Contact Length - Post-	Manufacturer	Molex, LLC
Package-SeriesC-Grid? 71979Connector TypeReceptacleConnector TypeFemale SocketStyleBoard to Board or CableNumber of Positions16Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleMounting TypeSurface Mount, Right AngleFerminationSolderContact Finish - MatingGoldContact Finish Thickness - MatingIpin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Category	Connectors, Interconnects
SeriesC-Grid? 71979Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions16Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleTerminationSolderContact Finish - MatingGoldContact Finish - Mating5.101 (3.8µm)Insulation ColorJishin (0.38µm)Insulation Height0.266" (6.76mm)Contact Length - Post-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions16Number of Positions LoadedAllNumber of Rows0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleTerminationSolderContact Finish - MatingGoldContact Finish - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions16Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorIsjuin (0.38µm)Insulation Height0.266" (6.76mm)Contact Length - Post-	Series	C-Grid? 71979
StyleBoard to Board or CableNumber of Positions16Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Connector Type	Receptacle
Number of Positions 16 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Isulation Color Ispin (0.38µm) Insulation Height 0.266" (6.76mm) Contact Finish - Post -	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Style	Board to Board or Cable
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Number of Positions	16
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface Mount, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Pitch - Mating	0.100" (2.54mm)
Mounting TypeSurface Mount, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Mounting Type	Surface Mount, Right Angle
Contact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Termination	Solder
Contact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.266" (6.76mm)Contact Length - Post-	Contact Finish - Mating	Gold
Insulation Height0.266" (6.76mm)Contact Length - Post-	Contact Finish Thickness - Mating	15μin (0.38μm)
Contact Length - Post -	Insulation Color	Black
-	Insulation Height	0.266" (6.76mm)
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Length - Post	-
	Operating Temperature	-40°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	Board Guide, Pick and Place
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 0719790208, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com