

0791077205 Information

Heisener.com

For Reference Only

Part Number 0791077205 **Manufacturer** Molex, LLC

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RCPT VERT DUAL 12CKT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0791077205 Specifications

Manufacturer Part Number 0791077205 Manufacturer Molex, LLC Category Connectors, Interconnects Package - Series Milli-Grid? 79107 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Testening Type Push-Pull Contact Finish - Mating Golder Contact Finish Thickness - Mating 15µin (0.38µm) Insulation Color Black Insulation Height 0.175" (4.45mm) Operating Temperature -55°C ~ 125°C Material Flammability Rating -		
Category Connectors, Interconnects Package - Series Milli-Grid? 79107 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm) Insulation Color Black Insulation Height 0.175" (4.45mm) Contact Length - Post 0.075" (1.91mm) Operating Temperature -55°C ~ 125°C	Manufacturer Part Number	0791077205
Package-SeriesMilli-Grid? 79107Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions12Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.175" (4.45mm)Contact Length - Post0.075" (1.91mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Molex, LLC
Package - Series Milli-Grid? 79107 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm) Insulation Color Black Insulation Height 0.175" (4.45mm) Contact Length - Post 0.075" (1.91mm) Operating Temperature -55°C ~ 125°C	Category	Connectors, Interconnects
Series Milli-Grid? 79107 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 15μin (0.38μm) Insulation Color Black Insulation Height 0.175" (4.45mm) Contact Length - Post 0.075" (1.91mm) Operating Temperature -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions12Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.175" (4.45mm)Contact Length - Post0.075" (1.91mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions12Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.175" (4.45mm)Contact Length - Post0.075" (1.91mm)Operating Temperature-55°C ~ 125°C	Series	Milli-Grid? 79107
StyleBoard to Board or CableNumber of Positions12Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.175" (4.45mm)Contact Length - Post0.075" (1.91mm)Operating Temperature-55°C ~ 125°C	Connector Type	Receptacle
Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm) Insulation Color Black Insulation Height 0.175" (4.45mm) Contact Length - Post 0.075" (1.91mm) Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.175" (4.45mm)Contact Length - Post0.075" (1.91mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm) Insulation Color Black Insulation Height 0.175" (4.45mm) Contact Length - Post 0.075" (1.91mm) Operating Temperature -55°C ~ 125°C	Number of Positions	12
Number of Rows2Row Spacing - Mating $0.079"$ ($2.00mm$)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $15\mu in$ ($0.38\mu m$)Insulation ColorBlackInsulation Height $0.175"$ ($4.45mm$)Contact Length - Post $0.075"$ ($1.91mm$)Operating Temperature -55° C ~ 125° C	Number of Positions Loaded	All
Row Spacing - Mating $0.079"$ ($2.00mm$)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating 15μ in (0.38μ m)Insulation ColorBlackInsulation Height $0.175"$ ($4.45mm$)Contact Length - Post $0.075"$ ($1.91mm$)Operating Temperature -55° C ~ 125° C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.175" (4.45mm)Contact Length - Post0.075" (1.91mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $15μin (0.38μm)$ Insulation ColorBlackInsulation Height $0.175" (4.45mm)$ Contact Length - Post $0.075" (1.91mm)$ Operating Temperature -55 °C ~ 125 °C	Row Spacing - Mating	0.079" (2.00mm)
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 15 μ in (0.38 μ m) Insulation Color Black Insulation Height 0.175" (4.45mm) Contact Length - Post 0.075" (1.91mm) Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - Mating Gold Contact Finish Thickness - Mating 15 μ in (0.38 μ m) Insulation Color Black Insulation Height 0.175" (4.45mm) Contact Length - Post 0.075" (1.91mm) Operating Temperature -55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating 15 μ in (0.38 μ m) Insulation Color Black Insulation Height 0.175" (4.45mm) Contact Length - Post 0.075" (1.91mm) Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.175"$ (4.45mm)Contact Length - Post $0.075"$ (1.91mm)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish - Mating	Gold
Insulation Height $0.175'' (4.45 \text{mm})$ Contact Length - Post $0.075'' (1.91 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	15μin (0.38μm)
Contact Length - Post $0.075" (1.91 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.175" (4.45mm)
	Contact Length - Post	0.075" (1.91mm)
Material Flammability Rating -	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	-

Contact Finish - Post	Tin	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
	Report error	rs?

0791077205 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0791077205 Payment Methods



















0791077205 Shipping Methods













If you have any question about 0791077205, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com