



08051U9R1DAT2A Information



For Reference Only

Part Number 08051U9R1DAT2A Manufacturer AVX Corporation

Category Capacitors
Ceramic Capacitors

Description CAP CER 9.1PF 100V NP0 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









08051U9R1DAT2A Specifications

Manufacturer Part Number08051U9R1DAT2AManufacturerAVX CorporationCategoryCapacitorsPackageCeramic CapacitorsPackage0805 (2012 Metric)SeriesUCapacitance9.1pFTolerance±0.5pFVoltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesUltra-Low ESR		
Category Capacitors Package 0805 (2012 Metric) Series U Capacitance 9.1pF Tolerance ±0.5pF Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C	er Part Number	08051U9R1DAT2A
Ceramic CapacitorsPackage $0805 (2012 \text{ Metric})$ SeriesUCapacitance 9.1pF Tolerance $\pm 0.5 \text{pF}$ Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	rer	AVX Corporation
Package $0805 (2012 \text{ Metric})$ Series U Capacitance 9.1pF Tolerance $\pm 0.5 \text{pF}$ Voltage - Rated 100V Temperature Coefficient $C0G, NP0$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$		Capacitors
Series U Capacitance 9.1pF Tolerance ± 0.5 pF Voltage - Rated 100V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C		Ceramic Capacitors
Capacitance $9.1 \mathrm{pF}$ Tolerance $\pm 0.5 \mathrm{pF}$ Voltage - Rated $100 \mathrm{V}$ Temperature Coefficient COG , NPOOperating Temperature $-55^{\circ}\mathrm{C} \sim 125^{\circ}\mathrm{C}$		0805 (2012 Metric)
Tolerance $\pm 0.5 pF$ Voltage - Rated $100V$ Temperature Coefficient $C0G$, NP0 Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$		U
Voltage - Rated $100V$ Temperature Coefficient $C0G$, NP0 Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	e	9.1pF
Temperature Coefficient C0G, NP0 Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$		±0.5pF
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	ated	100V
	re Coefficient	C0G, NP0
Features Ultra-Low ESR	Геmperature	-55°C ~ 125°C
		Ultra-Low ESR
Ratings -		-
Applications RF, Microwave, High Frequency	ıs	RF, Microwave, High Frequency
Failure Rate -	e	-
Mounting Type Surface Mount, MLCC	Гуре	Surface Mount, MLCC
Package / Case 0805 (2012 Metric)	Case	0805 (2012 Metric)
Size / Dimension 0.079" L x 0.049" W (2.01mm x 1.25mm)	ension	0.079" L x 0.049" W (2.01mm x 1.25mm)
Height - Seated (Max) -	ated (Max)	-
Thickness (Max) 0.045" (1.15mm)	(Max)	0.045" (1.15mm)
Lead Spacing -	ng	-
Lead Style -		-
Report error		Report errors?

08051U9R1DAT2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

08051U9R1DAT2A Payment Methods

































If you have any question about 08051U9R1DAT2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com