

0805J0630183MXT

lest a Quote

0805J0630183MXT Information

Heisener.com	Part Number	0805J0630183MXT	
	Manufacturer	Knowles Syfer	
	Category	Capacitors Ceramic Capacitors	
	Description	CAP CER 0.018UF 63V X7R 0805	- PC
	Package	0805 (2012 Metric)	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Req

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0805J0630183MXT Specifications

ManufacturerKnowles SyferCapacitorsCaranic CapacitorsPackage8005 (2012 Metric)Series-Capacitance0018µFTolerance±20%Voltage - Rated63VTomperature CoefficientX7R (2R1)Operating Temperature55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsSufface Mount, MLCCPackage / Case6805 (2012 Metric)Nounting Type0805 (2012 Metric)Size / Dimension0.070° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max).Tickness (Max)0.051° (1.30mm)Lead Spacing.		
CategoryCapacitorsPackage0805 (2012 Metric)Series-Capacitance0.018µFColerance±20%Voltage - Rated63VCoperating Temperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsSurface Mount, MLCCFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.007° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051° (1.30mm)Lead Spacing-Lead Style-	Manufacturer Part Number	0805J0630183MXT
Ceranic CapacitorsPackage0805 (2012 Metric)Series-Capacitance0.018µFTolerance±20%Voltage - Rated63VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.051" (1.30mm)Height - Seated (Max)-Thickness (Max)-Lead Style-	Manufacturer	Knowles Syfer
Package0805 (2012 Metric)Series-Capacitance0.018μFTolerance±20%Voltage - Rated63VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsNutmotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.0079° L x 0.049° W (2.00mm x 1.25mm)Fight - Seated (Max)-Height - Seated (Max)-Thickness (Max)0.051° (1.30mm)Lead Spacing-Lead Style-	Category	Capacitors
Series-Capacitance0.018µFTolerance±20%Voltage Rated63VTemperature CoefficientX7R (2R1)Operating Temperature55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance0.018µFTolerance±20%Voltage - Rated63VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Spacing-Lead Style- <t< td=""><td>Package</td><td>0805 (2012 Metric)</td></t<>	Package	0805 (2012 Metric)
Tolerance±20%Voltage - Rated63VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0050° L x 0.049° W (2.00mm x 1.25mm)Size / Dimension0.051° (1.30mm)Height - Seated (Max)-Lead Style-	Series	-
Voltage - Rated63VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Capacitance	0.018µF
Temperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Tolerance	$\pm 20\%$
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Voltage - Rated	63V
FeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Height Seated (Max)-Case-Mathematication-Starter (Max)-Starter (Max)-	Temperature Coefficient	X7R (2R1)
Ratings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Features	Epoxy Mountable
Fill de Rate-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Applications	Automotive
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Package / Case	0805 (2012 Metric)
Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.051" (1.30mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0805J0630183MXT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0805J0630183MXT Payment Methods





If you have any question about 0805J0630183MXT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com