

0805J2500682MXT

0805J2500682MXT Information

| Contraction to the second seco | Part Number Manufacturer Category Description Package | 0805J2500682MXT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 6800PF 250V X7R 0805 0805 (2012 Metric) For the pricing/inventory/lead time, please contact | |
|--|---|---|-----------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0805J2500682MXT Specifications

| Manufacturer Part Number0805J2500682MXTManufacturer OKnowles SyferCategoryCapacitorsCategoryCeramic CapacitorsPackage0805 (2012 Metric)Package-Capacitance6800pFColerance±20%Voltage - Rated250VPeneprature CoefficientX7R (2R1)Operating Temperature=55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate- |
|--|
| CategoryCapacitorsCeramic CapacitorsPackage0805 (2012 Metric)Package-Capacitance6800pFFolerance±20%Voltage - Rated250VPerperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableApplicationsAutomotive |
| Ceramic CapacitorsPackage0805 (2012 Metric)Series-Capacitance6800pFFolerance±20%Voltage - Rated250VFemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| Package0805 (2012 Metric)Series-Capacitance6800pFFolerance±20%Voltage - Rated250VFemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| Series-Capacitance6800pFColerance±20%Voltage - Rated250VComperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| Capacitance6800pFFolerance±20%Voltage - Rated250VFemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| Folerance±20%Voltage - Rated250VFemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| Voltage - Rated250VCemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| Femperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| Deperating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| FeaturesEpoxy MountableRatings-ApplicationsAutomotive |
| Ratings-ApplicationsAutomotive |
| Applications Automotive |
| |
| - |
| |
| Mounting Type Surface Mount, MLCC |
| Package / Case 0805 (2012 Metric) |
| Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) |
| Height - Seated (Max) - |
| Chickness (Max) 0.051" (1.30mm) |
| Lead Spacing - |
| Lead Style - |
| Report errors? |

0805J2500682MXT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0805J2500682MXT Payment Methods



0805J2500682MXT Shipping Methods



If you have any question about 0805J2500682MXT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com