



0805J5000680MDR Information

Heisener.com

0805J5000680MDR Part Number Manufacturer Knowles Syfer

Category Capacitors Ceramic Capacitors

Description CAP CER 68PF 500V X7R 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0805J5000680MDR Specifications

Manufacturer Part Number 0805J5000680MDR Manufacturer Knowles Syfer Category Capacitors Package 0805 (2012 Metric) Series - Capacitance 68pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0805 (2012 Metric) Series - Capacitance 68pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0805J5000680MDR
Package 0805 (2012 Metric) Series - Capacitance 68pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 0805 (2012 Metric) Series - Capacitance 68pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 68pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 68pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Package	0805 (2012 Metric)
Tolerance ±20% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Capacitance	68pF
Temperature Coefficient A7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) Thickness (Max) 0.051" (1.30mm) Lead Spacing Lead Style -	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Voltage - Rated	500V
Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Features	High Temperature
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Applications	High Reliability
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.051" (1.30mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0805J5000680MDR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0805J5000680MDR Payment Methods



















0805J5000680MDR Shipping Methods













If you have any question about 0805J5000680MDR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com