



0805Y0160272GCR Information



For Reference Only

Part Number 0805Y0160272GCR
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 0805 **Package** 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0805Y0160272GCR Specifications

Manufacturer Part Number 0805Y0160272GCR Manufacturer Knowles Syfer Category Capacitors Package 0805 (2012 Metric) Series FlexiCap? Capacitance 2700pF Tolerance ±2% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package 0805 (2012 Metric) Series FlexiCap? Capacitance 2700pF Tolerance ±2% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0805Y0160272GCR
Package 0805 (2012 Metric) Series FlexiCap? Capacitance 2700pF Tolerance ±2% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 0805 (2012 Metric) Series FlexiCap? Capacitance 2700pF Tolerance ±2% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 2700pF Tolerance ±2% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 2700pF Tolerance ±2% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Package	0805 (2012 Metric)
Tolerance ±2% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated16VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-Lead Style-	Capacitance	2700pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style COG, NP0 (1B) COG, NP0 (1B) Soft Termination Applications Soft Termination Application Soft Termination Application Onto Temperature COG, NP0 (1B) Soft Termination Application Application Onto Temperature - Soft Termination Application Onto Temperature - Soft Termination Application Application Onto Temperature - Soft Termination Application Onto Temperature - Soft Termination Application Onto Temperature - Soft Termination Application Application Application Onto Temperature - Soft Termination Application Application Onto Temperature - Soft Termination Application Onto Temperature - Soft Termination Application Application Application Application Application Onto Temperature - Soft Termination Application Application	Tolerance	±2%
Operating Temperature Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Soft Termination 0.070	Voltage - Rated	16V
Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0 (1B)
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.051" (1.30mm) Lead Spacing - Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.051" (1.30mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0805Y0160272GCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0805Y0160272GCR Payment Methods



































If you have any question about 0805Y0160272GCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com