

0805Y1000121MCTE03

0805Y1000121MCTE03 Information



For Reference Only

Part Number 0805Y1000121MCTE03

ManufacturerKnowles SyferCategoryCapacitors

Ceramic Capacitors

Description CERAMIC CAP **Package** 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









$0805Y1000121MCTE03\ Specifications$

Manufacturer Part Number 0805Y1000121MCTE03 Manufacturer Knowles Syfer Category Capacitors Package 0805 (2012 Metric) Series FlexiCap? Capacitance 120pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0805 (2012 Metric) Series FlexiCap? Capacitance 120pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0805Y1000121MCTE03
Package O805 (2012 Metric) Series FlexiCap? Capacitance 120pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 0805 (2012 Metric) Series FlexiCap? Capacitance 120pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 120pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 120pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Package	0805 (2012 Metric)
Tolerance ±20% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style	Series	FlexiCap?
Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, Epoxy MountableRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.045" (1.15mm)Lead Spacing-Lead Style-	Capacitance	120pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style COG, NP0 Soft Termination, Epoxy Mountable 8	Tolerance	±20%
Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Voltage - Rated	100V
FeaturesSoft Termination, Epoxy MountableRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.045" (1.15mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings - Graphications - Boardflex Sensitive - Graphications	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Features	Soft Termination, Epoxy Mountable
Failure Rate - Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style	Ratings	-
Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.045" (1.15mm) Lead Spacing - Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.045" (1.15mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
•		Report errors?

0805Y1000121MCTE03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0805Y1000121MCTE03 Payment Methods





















0805Y1000121MCTE03 Shipping Methods













If you have any question about 0805Y1000121MCTE03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com