

0805Y1000270MCTE03

0805Y1000270MCTE03 Information



For Reference Only

Part Number 0805Y1000270MCTE03

ManufacturerKnowles SyferCategoryCapacitors

Ceramic Capacitors

Description CERAMIC CAP **Package** 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0805Y1000270MCTE03 Specifications

Manufacturer Part Number0805Y1000270MCTE03ManufacturerKnowles SyferCategoryCapacitorsPackage0805 (2012 Metric)SeriesFlexiCap?Capacitance27pFTolerance±20%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, Epoxy Mountable
Category Capacitors Ceramic Capacitors Package 0805 (2012 Metric) Series FlexiCap? Capacitance 27pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable
Ceramic CapacitorsPackage $0805 (2012 \text{ Metric})$ SeriesFlexiCap?Capacitance $27pF$ Tolerance $\pm 20\%$ Voltage - Rated $100V$ Temperature Coefficient $C0G, NP0$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ FeaturesSoft Termination, Epoxy Mountable
Package 0805 (2012 Metric) Series FlexiCap? Capacitance 27pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable
SeriesFlexiCap?Capacitance $27pF$ Tolerance $\pm 20\%$ Voltage - Rated $100V$ Temperature Coefficient $C0G, NP0$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesSoft Termination, Epoxy Mountable
Capacitance $27pF$ Tolerance $\pm 20\%$ Voltage - Rated $100V$ Temperature Coefficient $C0G, NPO$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesSoft Termination, Epoxy Mountable
Tolerance $\pm 20\%$ Voltage - Rated $100V$ Temperature Coefficient $C0G$, NP0 Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Soft Termination, Epoxy Mountable
Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, Epoxy Mountable
Temperature CoefficientC0G, NP0Operating Temperature -55° C $\sim 125^{\circ}$ CFeaturesSoft Termination, Epoxy Mountable
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Features Soft Termination, Epoxy Mountable
Features Soft Termination, Epoxy Mountable
Ratings -
Applications Boardflex Sensitive
Failure Rate -
Mounting Type Surface Mount
Package / Case 0805 (2012 Metric)
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm)
Height - Seated (Max)
Thickness (Max) 0.045" (1.15mm)
Lead Spacing -
Lead Style -
Report error

0805Y1000270MCTE03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0805Y1000270MCTE03 Payment Methods



















0805Y1000270MCTE03 Shipping Methods













If you have any question about 0805Y1000270MCTE03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com