

0857931012 Information



Part Number 0857931012 **Manufacturer** Molex, LLC

Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 1PORT 1000 BASE-T

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0857931012 Specifications

Manufacturer Part Number 0857931012 Manufacturer Molex, LLC Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series 85793 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.546" (13.87mm) LED Color Yellow, Green - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0°C ~ 70°C		
CategoryConnectors, InterconnectsModular Connectors - Jacks With MagneticsPackage-Series85793Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.546" (13.87mm)LED ColorYellow, Green - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialCopper AlloyContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer Part Number	0857931012
Package - Series 85793 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole 90° Angle (Right) Termination Solder Height Above Board 0.546" (13.87mm) LED Color Yellow, Green - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0°C ~ 70°C	Manufacturer	Molex, LLC
Package-Series85793Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.546" (13.87mm)LED ColorYellow, Green - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialCopper AlloyContact FinishGoldOperating Temperature0°C ~ 70°C	Category	Connectors, Interconnects
Series 85793 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.546" (13.87mm) LED Color Yellow, Green - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.546" (13.87mm)LED ColorYellow, Green - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialCopper AlloyContact FinishGoldOperating Temperature0°C ~ 70°C	Package	-
Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.546" (13.87mm) LED Color Yellow, Green - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature	Series	85793
Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.546" (13.87mm)LED ColorYellow, Green - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialCopper AlloyContact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board LED Color Yellow, Green - Green Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Contact Finish Operating Temperature 10/100/1000 Base-T, AutoMDIX Through Hole 10/2001 Solder 10/2004 10/2	Number of Ports	1
Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.546" (13.87mm)LED ColorYellow, Green - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialCopper AlloyContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 0.546" (13.87mm) LED Color Yellow, Green - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0°C ~ 70°C	Applications	10/100/1000 Base-T, AutoMDIX
Termination Solder Height Above Board 0.546" (13.87mm) LED Color Yellow, Green - Green Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature	Mounting Type	Through Hole
Height Above Board LED Color Yellow, Green - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0.546" (13.87mm) Yellow, Green - Green 8 Copper Alloy Shielded, EMI Finger Copper Alloy Copper Alloy Copper Alloy O°C ~ 70°C	Orientation	90° Angle (Right)
LED ColorYellow, Green - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialCopper AlloyContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Contact Finish Gold Operating Temperature 8 Cores per Jack Shielded, EMI Finger Board Lock Copper Alloy Copper Alloy Copper Alloy Contact Finish Operating Temperature 0°C ~ 70°C	Height Above Board	0.546" (13.87mm)
Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0°C ~ 70°C	LED Color	Yellow, Green - Green
Features Board Lock Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	8
Tab Direction Up Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0°C ~ 70°C	Shielding	Shielded, EMI Finger
Contact Material Copper Alloy Contact Finish Gold Operating Temperature 0°C ~ 70°C	Features	Board Lock
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Up
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	Copper Alloy
	Contact Finish	Gold
Report errors?	Operating Temperature	0°C ~ 70°C
		Report errors?

0857931012 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0857931012 Payment Methods





















0857931012 Shipping Methods













If you have any question about 0857931012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com