

### **0872634234 Information**

Heisener.com

For Reference Only

**Part Number** 0872634234 **Manufacturer** Molex, LLC

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** MGRID B/E REC SMT W/OPG GOLD 42C

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 0872634234 Specifications

Manufacturer Part Number         0872634234           Manufacturer         Molex, LLC           Category         Connectors, Interconnects           Rectangular Connectors - Headers, Receptacles, Female Sockets           Package         -           Series         Milli-Grid? 87263           Connector Type         Receptacle, Bottom Entry           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         42           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Surface Mount           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         15µin (0.38µm)           Insulation Height         0.110" (2.79mm)           Contact Length - Post         -           Operating Temperature         -55°C ~ 105°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         Milli-Grid? 87263           Connector Type         Receptacle, Bottom Entry           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         42           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Surface Mount           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         15µin (0.38µm)           Insulation Color         Black           Insulation Height         0.110" (2.79mm)           Contact Length - Post         -           Operating Temperature         -55°C ~ 105°C	Manufacturer Part Number	0872634234
Package       -         Series       Milli-Grid? 87263         Connector Type       Receptacle, Bottom Entry         Contact Type       Female Socket         Style       Board to Board or Cable         Number of Positions       42         Number of Positions Loaded       All         Pitch - Mating       0.079" (2.00mm)         Number of Rows       2         Row Spacing - Mating       0.079" (2.00mm)         Mounting Type       Surface Mount         Termination       Solder         Fastening Type       Push-Pull         Contact Finish - Mating       Gold         Contact Finish Thickness - Mating       15µin (0.38µm)         Insulation Color       Black         Insulation Height       0.110" (2.79mm)         Contact Length - Post       -         Operating Temperature       -55°C ~ 105°C	Manufacturer	Molex, LLC
Package         -           Series         Milli-Grid? 87263           Connector Type         Receptacle, Bottom Entry           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         42           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Surface Mount           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         15µin (0.38µm)           Insulation Color         Black           Insulation Height         0.110" (2.79mm)           Contact Length - Post         -           Operating Temperature         -55°C ~ 105°C	Category	Connectors, Interconnects
SeriesMilli-Grid? 87263Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPitch - Mating $0.079"$ ( $2.00mm$ )Number of Rows2Row Spacing - Mating $0.079"$ ( $2.00mm$ )Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $15\mu$ in ( $0.38\mu$ m)Insulation ColorBlackInsulation Height $0.110"$ ( $2.79mm$ )Contact Length - Post-Operating Temperature $-55°C \sim 105°C$		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPitch - Mating $0.079"$ ( $2.00mm$ )Number of Rows2Row Spacing - Mating $0.079"$ ( $2.00mm$ )Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $15\mu$ in ( $0.38\mu$ m)Insulation ColorBlackInsulation Height $0.110"$ ( $2.79mm$ )Contact Length - Post-Operating Temperature $-55°C \sim 105°C$	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15µin (0.38µm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post-Operating Temperature-55°C ~ 105°C	Series	Milli-Grid? 87263
StyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post-Operating Temperature-55°C ~ 105°C	Connector Type	Receptacle, Bottom Entry
Number of Positions42Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post-Operating Temperature-55°C ~ 105°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post-Operating Temperature-55°C ~ 105°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post-Operating Temperature-55°C ~ 105°C	Number of Positions	42
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post-Operating Temperature-55°C ~ 105°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post-Operating Temperature-55°C ~ 105°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post-Operating Temperature-55°C ~ 105°C	Number of Rows	2
Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 15 $\mu$ in (0.38 $\mu$ m)  Insulation Color Black  Insulation Height 0.110" (2.79mm)  Contact Length - Post -  Operating Temperature -55°C ~ 105°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 15 $\mu$ in (0.38 $\mu$ m)  Insulation Color Black  Insulation Height 0.110" (2.79mm)  Contact Length - Post -  Operating Temperature -55°C ~ 105°C	Mounting Type	Surface Mount
Contact Finish - Mating Gold  Contact Finish Thickness - Mating 15 $\mu$ in (0.38 $\mu$ m)  Insulation Color Black  Insulation Height 0.110" (2.79mm)  Contact Length - Post -  Operating Temperature -55°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Mating $15\mu$ in $(0.38\mu$ m)  Insulation Color Black  Insulation Height $0.110$ " $(2.79$ mm)  Contact Length - Post -  Operating Temperature $-55$ °C $\sim 105$ °C	Fastening Type	Push-Pull
Insulation Color  Black Insulation Height  0.110" (2.79mm)  Contact Length - Post  Operating Temperature  -55°C ~ 105°C	Contact Finish - Mating	Gold
Insulation Height $0.110'' (2.79 \text{mm})$ Contact Length - Post - Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	15μin (0.38μm)
Contact Length - Post - Operating Temperature -55°C ~ 105°C	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.110" (2.79mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 105°C
to the state of th	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### **0872634234 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 0872634234 Payment Methods



















# 0872634234 Shipping Methods













If you have any question about 0872634234, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com