



0874002.MXEP Information

Part Number 0874002.MXEP Manufacturer Littelfuse Inc. Category Circuit Protection

Fuses

Description FUSE CERAMIC 2A 250VAC AXIAL

Package Cartridge, Non-Standard (Axial)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0874002.MXEP Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Package Cartridge, Non-Standard (Axial) Series 874 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Fast Package / Case Cartridge, Non-Standard (Axial) Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals Operating Temperature -55°C ~ 125°C	•	
Category Circuit Protection Fuses Package Cartridge, Non-Standard (Axial) Series 874 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Circuit Protection Fuses Cartridge, Non-Standard (Axial) Through Hole SoA	Manufacturer Part Number	0874002.MXEP
Fuses Package Cartridge, Non-Standard (Axial) Series 874 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 1.812 Approvals cULus	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard (Axial) Series 874 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting 12t 1.812 Approvals cULus	Category	Circuit Protection
Series 874 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 1.812 Approvals cULus		Fuses
Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 1.812 Approvals cULus	Package	Cartridge, Non-Standard (Axial)
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals 2A 250V Cartridge, Non-Standard (Axial) Through Hole 50A Cartridge, Non-Standard (Axial) Cartridge, Non-Standard (Axial)	Series	874
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals 250V Cartridge, Non-Standard (Axial) Through Hole 50A Cartridge, Non-Standard (Axial)	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CULus	Current Rating	2A
Response Time Fast Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 1.812 Approvals cULus	Voltage Rating - AC	250V
Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 1.812 Approvals cULus	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals Through Hole 50A L812 CULus	Response Time	Fast
Breaking Capacity @ Rated Voltage 50A Melting I2t 1.812 Approvals cULus	Package / Case	Cartridge, Non-Standard (Axial)
Melting I2t 1.812 Approvals cULus	Mounting Type	Through Hole
Approvals cULus	Breaking Capacity @ Rated Voltage	50A
11	Melting I2t	1.812
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Approvals	cULus
	Operating Temperature	-55°C ~ 125°C
Color -	Color	-
Size / Dimension 0.142" Dia x 0.394" L (3.60mm x 10.00mm)	Size / Dimension	0.142" Dia x 0.394" L (3.60mm x 10.00mm)
Report errors?		Report errors?

0874002.MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0874002.MXEP Payment Methods



















0874002.MXEP Shipping Methods













If you have any question about 0874002.MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com