



087502.5MXEP Information



For Reference Only

Part Number 087502.5MXEP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE CERAMIC 2.5A 250VAC AXIAL

Package Cartridge, Non-Standard (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









087502.5MXEP Specifications

Manufacturer Part Number087502.5MXEPManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackageCartridge, Non-Standard (Axial)Series875Fuse TypeCartridge, CeramicCurrent Rating2.5AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseCartridge, Non-Standard (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage50AMelting I2t17.85ApprovalscULusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.142" Dia x 0.394" L (3.60mm x 10.00mm)	•	
Category Circuit Protection Fuses Package Cartridge, Non-Standard (Axial) Series 875 Fuse Type Cartridge, Ceramic Current Rating 2.5A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Non-Standard (Axial) Culus Onesting Temperature -55°C ~ 125°C Olon O.142" Dia x 0.394" L (3.60mm x 10.00mm)	Manufacturer Part Number	087502.5MXEP
Fuses Package Cartridge, Non-Standard (Axial) Series 875 Fuse Type Cartridge, Ceramic Current Rating 2.5A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Non-Standard (Axial) 17.85 Cartridge, Non-Standard (Axial) 17.85 Color Color -10.12°C Cartridge, Non-Standard (Axial) 17.85 Cartridge, Non-Standard (Axial)	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard (Axial) Series 875 Fuse Type Cartridge, Ceramic Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 17.85 Approvals cULus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.142" Dia x 0.394" L (3.60mm x 10.00mm)	Category	Circuit Protection
Series 875 Fuse Type Cartridge, Ceramic Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 17.85 Approvals cULus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.142" Dia x 0.394" L (3.60mm x 10.00mm)		Fuses
Fuse Type Current Rating 2.5A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Non-Standard (Axial)	Package	Cartridge, Non-Standard (Axial)
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 17.85 Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension 2.5A 250V Color Color 250V Color 2500 2500 2500 2500 2500 Color Color	Series	875
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Color Size / Dimension 250V Cartridge, Non-Standard (Axial) Through Hole Cartridge, Non-Standard (Axial) Through Hole 50A 17.85 CuLus Operating Temperature -55°C ~ 125°C Color - Size / Dimension	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 17.85 Approvals Operating Temperature -55°C ~ 125°C Color - Size / Dimension Outpublic Color - Size / Dimension - Slow Cartridge, Non-Standard (Axial) Through Hole 50A Culus 50A 17.85 Culus -55°C ~ 125°C 0.142" Dia x 0.394" L (3.60mm x 10.00mm)	Current Rating	2.5A
Response Time Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 17.85 Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow Cartridge, Non-Standard (Axial) Through Hole 50A Cartridge, Non-Standard (Axial) Through Hole 50A 17.85 Color -185°C -125°C -125°C -125°C -125°C	Voltage Rating - AC	250V
Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 17.85 Approvals CULus Operating Temperature -55°C ~ 125°C Color - Size / Dimension Cartridge, Non-Standard (Axial) Through Hole 50A 17.85 20Lus 17.85 20Lus	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage 50A Melting I2t 17.85 Approvals Operating Temperature Color Size / Dimension Through Hole 50A 17.85 cULus -55°C ~ 125°C -125°C 0.142" Dia x 0.394" L (3.60mm x 10.00mm)	Response Time	Slow
Breaking Capacity @ Rated Voltage 50A Melting I2t 17.85 Approvals cULus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.142" Dia x 0.394" L (3.60mm x 10.00mm)	Package / Case	Cartridge, Non-Standard (Axial)
Melting I2t 17.85 ApprovalscULusOperating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color-Size / Dimension 0.142° Dia x 0.394° L $(3.60 \text{mm} \times 10.00 \text{mm})$	Mounting Type	Through Hole
Approvals cULus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.142" Dia x 0.394" L (3.60mm x 10.00mm)	Breaking Capacity @ Rated Voltage	50A
Operating Temperature	Melting I2t	17.85
Color - Size / Dimension - 0.142" Dia x 0.394" L (3.60mm x 10.00mm)	Approvals	cULus
Size / Dimension 0.142" Dia x 0.394" L (3.60mm x 10.00mm)	Operating Temperature	-55°C ~ 125°C
, and the second se	Color	-
	Size / Dimension	0.142" Dia x 0.394" L (3.60mm x 10.00mm)
Report errors?		Report errors?

087502.5MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

087502.5MXEP Payment Methods



















087502.5MXEP Shipping Methods













If you have any question about 087502.5MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com