

## **0936010904 Information**

Heisener.com

**Part Number** 0936010904 Manufacturer Molex, LLC

Category Connectors, Interconnects

Heavy Duty Connectors - Housings, Hoods, Bases

**Description** CONN HOOD TOP ENTRY SZ6B PG16

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









093	36010	0904 S	Spec	eifica	tions
	_				

Manufacturer Part Number         0936010904           Manufacturer         Molex, LLC           Category         Connectors, Interconnects           Package         -           Series         GWconnect?           Connector Type         Hood           Style         Top Entry           Size         6B           Lock Location         Locking Clip (1) on Base Bottom           Thread Size         PG16           Size / Dimension         2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)           Housing Color         -           Features         -           Ingress Protection         IP66 - Dust Tight, Water Resistant           Housing Material         Aluminum Alloy, Die Cast           Housing Finish         Powder Coated           Operating Temperature         -40°C ~ 125°C	ose out of a specifications		
CategoryConnectors, InterconnectsHeavy Duty Connectors - Housings, Hoods, BasesPackage-SeriesGWconnect?Connector TypeHoodStyleTop EntrySize6BLock LocationLocking Clip (1) on Base BottomThread SizePG16Size / Dimension2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Manufacturer Part Number	0936010904	
Heavy Duty Connectors - Housings, Hoods, Bases  Package - Series GWconnect?  Connector Type Hood Style Top Entry  Size 6B Lock Location Locking Clip (1) on Base Bottom  Thread Size PG16 Size / Dimension 2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)  Housing Color Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Housing Finish Powder Coated  Operating Temperature - 40°C ~ 125°C	Manufacturer	Molex, LLC	
Package-SeriesGWconnect?Connector TypeHoodStyleTop EntrySize6BLock LocationLocking Clip (1) on Base BottomThread SizePG16Size / Dimension2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Category	Connectors, Interconnects	
Series GWconnect?  Connector Type Hood  Style Top Entry  Size 6B  Lock Location Locking Clip (1) on Base Bottom  Thread Size PG16  Size / Dimension 2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C		Heavy Duty Connectors - Housings, Hoods, Bases	
Connector TypeHoodStyleTop EntrySize6BLock LocationLocking Clip (1) on Base BottomThread SizePG16Size / Dimension2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Package	-	
Style Top Entry Size 6B  Lock Location Locking Clip (1) on Base Bottom  Thread Size PG16 Size / Dimension 2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)  Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Series	GWconnect?	
Size 6B  Lock Location Locking Clip (1) on Base Bottom  Thread Size PG16  Size / Dimension 2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)  Housing Color - Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Connector Type	Hood	
Lock LocationLocking Clip (1) on Base BottomThread SizePG16Size / Dimension2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Style	Top Entry	
Thread Size PG16 Size / Dimension 2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size	6B	
Size / Dimension 2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Lock Location	Locking Clip (1) on Base Bottom	
Housing Color  Features  Ingress Protection  IP66 - Dust Tight, Water Resistant  Housing Material  Aluminum Alloy, Die Cast  Housing Finish  Powder Coated  Operating Temperature  -40°C ~ 125°C	Thread Size	PG16	
Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size / Dimension	2.362" L x 1.713" W x 2.087" H (60.00mm x 43.50mm x 53.00mm)	
Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Housing Color	-	
Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-	
Housing Finish Powder Coated  Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Ingress Protection	IP66 - Dust Tight, Water Resistant	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Housing Material	Aluminum Alloy, Die Cast	
	Housing Finish	Powder Coated	
Report errors?	Operating Temperature	-40°C ~ 125°C	
			Report errors?

#### 0936010904 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0936010904 Payment Methods



















## 0936010904 Shipping Methods













If you have any question about 0936010904, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com