

# 0936010964 Information

Heisener.com

**Part Number** 0936010964 **Manufacturer** Molex, LLC

Category Connectors, Interconnects

Heavy Duty Connectors - Housings, Hoods, Bases

**Description** CONN BASE SIDE ENTRY SZ6B PG29

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 0936010964 Specifications

Manufacturer Part Number         0936010964           Manufacturer         Molex, LLC           Category         Connectors, Interconnects           Heavy Duty Connectors - Housings, Hoods, Bases           Package         -           Series         GWconnect?           Connector Type         Base - Box Mount           Style         Side Entry           Size         6B           Lock Location         Locking Clip (1) on Base Bottom           Thread Size         PG29           Size / Dimension         3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)           Housing Color         -           Features         Feed Through           Ingress Protection         IP66 - Dust Tight, Water Resistant           Housing Material         Aluminum Alloy, Die Cast           Housing Finish         Powder Coated           Operating Temperature         -40°C ~ 125°C	ose out of a pecifications		
CategoryConnectors, InterconnectsHeavy Duty Connectors - Housings, Hoods, BasesPackage-SeriesGWconnect?Connector TypeBase - Box MountStyleSide EntrySize6BLock LocationLocking Clip (1) on Base BottomThread SizePG29Size / Dimension3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)Housing Color-FeaturesFeed ThroughIngress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Manufacturer Part Number	0936010964	
Heavy Duty Connectors - Housings, Hoods, Bases  Package - Series GWconnect? Connector Type Base - Box Mount  Style Side Entry  Size 6B Lock Location Locking Clip (1) on Base Bottom  Thread Size PG29 Size / Dimension 3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)  Housing Color Features Feed Through Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Manufacturer	Molex, LLC	
Package-SeriesGWconnect?Connector TypeBase - Box MountStyleSide EntrySize6BLock LocationLocking Clip (1) on Base BottomThread SizePG29Size / Dimension3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)Housing Color-FeaturesFeed ThroughIngress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Category	Connectors, Interconnects	
Series GWconnect?  Connector Type Base - Box Mount  Style Side Entry  Size 6B  Lock Location Locking Clip (1) on Base Bottom  Thread Size PG29  Size / Dimension 3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)  Housing Color -  Features Feed Through  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C		Heavy Duty Connectors - Housings, Hoods, Bases	
Connector TypeBase - Box MountStyleSide EntrySize6BLock LocationLocking Clip (1) on Base BottomThread SizePG29Size / Dimension3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)Housing Color-FeaturesFeed ThroughIngress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Package	-	
Style Side Entry  Size 6B  Lock Location Locking Clip (1) on Base Bottom  Thread Size PG29  Size / Dimension 3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)  Housing Color -  Features Feed Through  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Series	GWconnect?	
Size 6B  Lock Location Locking Clip (1) on Base Bottom  Thread Size PG29  Size / Dimension 3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)  Housing Color -  Features Feed Through  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Connector Type	Base - Box Mount	
Lock LocationLocking Clip (1) on Base BottomThread SizePG29Size / Dimension3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)Housing Color-FeaturesFeed ThroughIngress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Style	Side Entry	
Thread Size PG29 Size / Dimension 3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm) Housing Color - Features Feed Through Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size	6B	
Size / Dimension 3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)  Housing Color -  Features Feed Through  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Lock Location	Locking Clip (1) on Base Bottom	
Housing Color  Features  Feed Through  Ingress Protection  IP66 - Dust Tight, Water Resistant  Housing Material  Aluminum Alloy, Die Cast  Housing Finish  Powder Coated  Operating Temperature  -40°C ~ 125°C	Thread Size	PG29	
Features Feed Through Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size / Dimension	3.287" L x 2.244" W x 3.110" H (83.50mm x 57.00mm x 79.00mm)	
Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Housing Color	-	
Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	Feed Through	
Housing Finish Powder Coated  Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Ingress Protection	IP66 - Dust Tight, Water Resistant	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Housing Material	Aluminum Alloy, Die Cast	
	Housing Finish	Powder Coated	
Report errors?	Operating Temperature	-40°C ~ 125°C	
			Report errors?

### 0936010964 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 0936010964 Payment Methods





















# 0936010964 Shipping Methods













If you have any question about 0936010964, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com