

### 0936012201 Information

Heisener.com

**Part Number** 0936012201 **Manufacturer** Molex, LLC

Category Connectors, Interconnects

Heavy Duty Connectors - Housings, Hoods, Bases

**Description** CONN HOOD SIDE ENTRY SZ16A M20

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# $0936012201\ Specifications$

Manufacturer Part Number         0936012201           Manufacturer         Molex, LLC           Category         Connectors, Interconnects           Heavy Duty Connectors - Housings, Hoods, Bases           Package         -           Series         GWconnect?           Connector Type         Hood           Style         Side Entry           Size         16A           Lock Location         Locking Clip (1) on Base Bottom           Thread Size         M20           Size / Dimension         3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)           Housing Color         -           Features         -           Ingress Protection         IP66 - Dust Tight, Water Resistant           Housing Material         Aluminum Alloy, Die Cast           Housing Finish         Powder Coated           Operating Temperature         -40°C ~ 125°C	ose ou 12201 specimentions		
CategoryConnectors, InterconnectsHeavy Duty Connectors - Housings, Hoods, BasesPackage-SeriesGWconnect?Connector TypeHoodStyleSide EntrySize16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Manufacturer Part Number	0936012201	
Heavy Duty Connectors - Housings, Hoods, Bases  Package - Series GWconnect? Connector Type Hood Style Side Entry Size 16A Lock Location Locking Clip (1) on Base Bottom Thread Size M20 Size / Dimension 3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm) Housing Color Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature - 40°C ~ 125°C	Manufacturer	Molex, LLC	
Package-SeriesGWconnect?Connector TypeHoodStyleSide EntrySize16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Category	Connectors, Interconnects	
Series GWconnect?  Connector Type Hood  Style Side Entry  Size 16A  Lock Location Locking Clip (1) on Base Bottom  Thread Size M20  Size / Dimension 3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C		Heavy Duty Connectors - Housings, Hoods, Bases	
Connector TypeHoodStyleSide EntrySize16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Package	-	
Style Side Entry  Size 16A  Lock Location Locking Clip (1) on Base Bottom  Thread Size M20  Size / Dimension 3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Series	GWconnect?	
Size 16A  Lock Location Locking Clip (1) on Base Bottom  Thread Size M20  Size / Dimension 3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)  Housing Color - Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Connector Type	Hood	
Lock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Style	Side Entry	
Thread Size M20 Size / Dimension 3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size	16A	
Size / Dimension 3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Lock Location	Locking Clip (1) on Base Bottom	
Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Thread Size	M20	
Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size / Dimension	3.130" L x 1.165" W x 2.362" H (79.50mm x 29.60mm x 60.00mm)	
Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature $-40^{\circ}$ C ~ $125^{\circ}$ C	Housing Color	-	
Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-	
Housing Finish Powder Coated  Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Ingress Protection	IP66 - Dust Tight, Water Resistant	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Housing Material	Aluminum Alloy, Die Cast	
	Housing Finish	Powder Coated	
Report errors?	Operating Temperature	-40°C ~ 125°C	
			Report errors?

### 0936012201 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0936012201 Payment Methods


































If you have any question about 0936012201, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com