

0936012789 Information

Heisener.com

Part Number 0936012789 **Manufacturer** Molex, LLC

Category Connectors, Interconnects

Heavy Duty Connectors - Housings, Hoods, Bases

Description CONN HOOD TOP ENTRY SZ16B PG21

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0936012789 Specifications

| Manufacturer Part Number 0936012789 Manufacturer Molex, LLC Category Connectors, Interconnects Heavy Duty Connectors - Housings, Hoods, Bases Package - Series GWconnect? Connector Type Hood Style Top Entry Size 16B Lock Location Locking Clip (2) on Hood Top Thread Size PG21 Size / Dimension 3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C | oscool270s specifications | | |
|--|---------------------------|--|----------------|
| CategoryConnectors, InterconnectsHeavy Duty Connectors - Housings, Hoods, BasesPackage-SeriesGWconnect?Connector TypeHoodStyleTop EntrySize16BLock LocationLocking Clip (2) on Hood TopThread SizePG21Size / Dimension3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C | Manufacturer Part Number | 0936012789 | |
| Heavy Duty Connectors - Housings, Hoods, Bases Package - Series GWconnect? Connector Type Hood Style Top Entry Size 16B Lock Location Locking Clip (2) on Hood Top Thread Size PG21 Size / Dimension 3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm) Housing Color Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Housing Finish Powder Coated Operating Temperature - 40°C ~ 125°C | Manufacturer | Molex, LLC | |
| Package-SeriesGWconnect?Connector TypeHoodStyleTop EntrySize16BLock LocationLocking Clip (2) on Hood TopThread SizePG21Size / Dimension3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C | Category | Connectors, Interconnects | |
| Series GWconnect? Connector Type Hood Style Top Entry Size 16B Lock Location Locking Clip (2) on Hood Top Thread Size PG21 Size / Dimension 3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C | | Heavy Duty Connectors - Housings, Hoods, Bases | |
| Connector TypeHoodStyleTop EntrySize16BLock LocationLocking Clip (2) on Hood TopThread SizePG21Size / Dimension3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C | Package | - | |
| Style Top Entry Size 16B Lock Location Locking Clip (2) on Hood Top Thread Size PG21 Size / Dimension 3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C | Series | GWconnect? | |
| Size 16B Lock Location Locking Clip (2) on Hood Top Thread Size PG21 Size / Dimension 3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C | Connector Type | Hood | |
| Lock LocationLocking Clip (2) on Hood TopThread SizePG21Size / Dimension3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C | Style | Top Entry | |
| Thread Size PG21 Size / Dimension 3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C | Size | 16B | |
| Size / Dimension 3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C | Lock Location | Locking Clip (2) on Hood Top | |
| Housing Color Features Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C | Thread Size | PG21 | |
| Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C | Size / Dimension | 3.701" L x 1.713" W x 2.520" H (94.00mm x 43.50mm x 64.00mm) | |
| Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature -40° C ~ 125° C | Housing Color | - | |
| Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Features | - | |
| Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Ingress Protection | IP66 - Dust Tight, Water Resistant | |
| Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Housing Material | Aluminum Alloy, Die Cast | |
| | Housing Finish | Powder Coated | |
| Report errors? | Operating Temperature | -40°C ~ 125°C | |
| | | | Report errors? |

0936012789 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0936012789 Payment Methods



















0936012789 Shipping Methods













If you have any question about 0936012789, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com