

## 0936012801 Information

Heisener.com

**Part Number** 0936012801 **Manufacturer** Molex, LLC

**Category** Connectors, Interconnects

Heavy Duty Connectors - Housings, Hoods, Bases

**Description** CONN HOOD TOP ENTRY SZ16B M32

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0936012801	<b>Specifications</b>

Manufacturer Part Number0936012801ManufacturerMolex, LLCCategoryConnectors, InterconnectsHeavy Duty Connectors - Housings, Hoods, BasesPackage-SeriesGWconnect?Connector TypeHoodStyleTop EntrySize16BLock LocationLocking Clip (1) on Base BottomThread SizeM32Size / Dimension3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C			
Category  Connectors, Interconnects  Heavy Duty Connectors - Housings, Hoods, Bases  Package  - Series  GWconnect?  Connector Type  Hood  Style  Top Entry  Size  16B  Lock Location  Locking Clip (1) on Base Bottom  Thread Size  M32  Size / Dimension  3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)  Housing Color  Features  - Features  - Ingress Protection  IP66 - Dust Tight, Water Resistant  Housing Material  Aluminum Alloy, Die Cast  Housing Finish  Powder Coated  Operating Temperature  - 40°C ~ 125°C	Manufacturer Part Number	0936012801	
Package-SeriesGWconnect?Connector TypeHoodStyleTop EntrySize16BLock LocationLocking Clip (1) on Base BottomThread SizeM32Size / Dimension3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Manufacturer	Molex, LLC	
Package - GWconnect?  Connector Type Hood  Style Top Entry  Size 16B  Lock Location Locking Clip (1) on Base Bottom  Thread Size M32  Size / Dimension 3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)  Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature - 40°C ~ 125°C	Category	Connectors, Interconnects	
Series GWconnect?  Connector Type Hood  Style Top Entry  Size 16B  Lock Location Locking Clip (1) on Base Bottom  Thread Size M32  Size / Dimension 3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C		Heavy Duty Connectors - Housings, Hoods, Bases	
Connector Type Hood  Style Top Entry  Size 16B  Lock Location Locking Clip (1) on Base Bottom  Thread Size M32  Size / Dimension 3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Package	-	
Style Top Entry  Size 16B  Lock Location Locking Clip (1) on Base Bottom  Thread Size M32  Size / Dimension 3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)  Housing Color -  Features - Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Series	GWconnect?	
Size 16B  Lock Location Locking Clip (1) on Base Bottom  Thread Size M32  Size / Dimension 3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Connector Type	Hood	
Lock LocationLocking Clip (1) on Base BottomThread SizeM32Size / Dimension3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)Housing Color-Features-Ingress ProtectionIP66 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Style	Top Entry	
Thread Size M32 Size / Dimension 3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm) Housing Color - Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size	16B	
Size / Dimension 3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)  Housing Color -  Features -  Ingress Protection IP66 - Dust Tight, Water Resistant  Housing Material Aluminum Alloy, Die Cast  Housing Finish Powder Coated  Operating Temperature -40°C ~ 125°C	Lock Location	Locking Clip (1) on Base Bottom	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Thread Size	M32	
Features - Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Size / Dimension	3.701" L x 1.713" W x 2.283" H (94.00mm x 43.50mm x 58.00mm)	
Ingress Protection IP66 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Housing Color	-	
Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-	
Housing Finish Powder Coated  Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Ingress Protection	IP66 - Dust Tight, Water Resistant	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Housing Material	Aluminum Alloy, Die Cast	
	Housing Finish	Powder Coated	
Deposit among	Operating Temperature	-40°C ~ 125°C	
keport errors?			Report errors?

#### 0936012801 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0936012801 Payment Methods



















## 0936012801 Shipping Methods













If you have any question about 0936012801, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com