

09465004400 Information



For Reference Only

Part Number 09465004400 **Manufacturer** HARTING

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description HPP V4 POWER INSERT THT 48V/12A

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









09465004400 Specifications

Manufacturer Part Number 09465004400 Manufacturer HARTING Category Connectors, Interconnects Package - Series Han? PushPull Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 (Power) Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post - Operating Temperature - Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series Han? PushPull Connector Type - Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 (Power) Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post - Operating Temperature -40°C ~ 70°C	Manufacturer Part Number	09465004400
Package-SeriesHan? PushPullConnector Type-Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions4 (Power)Number of Positions LoadedAllPitch - Mating-Number of Rows2Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating-Contact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.469" (11.90mm)Contact Length - Post-Operating Temperature-40°C ~ 70°C	Manufacturer	HARTING
Package - Series Han? PushPull Connector Type - Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 (Power) Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post - Operating Temperature -40°C ~ 70°C	Category	Connectors, Interconnects
SeriesHan? PushPullConnector Type-Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions4 (Power)Number of Positions LoadedAllPitch - Mating-Number of Rows2Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating-Contact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.469" (11.90mm)Contact Length - Post-Operating Temperature-40°C ~ 70°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type-Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions4 (Power)Number of Positions LoadedAllPitch - Mating-Number of Rows2Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating-Contact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.469" (11.90mm)Contact Length - Post-Operating Temperature-40°C ~ 70°C	Package	-
Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions4 (Power)Number of Positions LoadedAllPitch - Mating-Number of Rows2Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating-Contact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.469" (11.90mm)Contact Length - Post-Operating Temperature-40°C ~ 70°C	Series	Han? PushPull
Style Board to Cable/Wire Number of Positions 4 (Power) Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height O.469" (11.90mm) Contact Length - Post - Operating Temperature -40°C ~ 70°C	Connector Type	-
Number of Positions 4 (Power) Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height O.469" (11.90mm) Contact Length - Post - Operating Temperature -40°C ~ 70°C	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating - Number of Rows 2 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.469" (11.90mm) Contact Length - Post Operating Temperature -40°C ~ 70°C	Style	Board to Cable/Wire
Pitch - Mating-Number of Rows2Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating-Contact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.469" (11.90mm)Contact Length - Post-Operating Temperature-40°C ~ 70°C	Number of Positions	4 (Power)
Number of Rows Row Spacing - Mating Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post Operating Temperature -40°C ~ 70°C	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.469" (11.90mm) Contact Length - Post Operating Temperature -40°C ~ 70°C	Pitch - Mating	-
Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post - Operating Temperature -40°C ~ 70°C	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post - Operating Temperature -40°C ~ 70°C	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post - Operating Temperature -40°C ~ 70°C	Mounting Type	Through Hole, Right Angle
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post Operating Temperature -40°C ~ 70°C	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.469" (11.90mm) Contact Length - Post - Operating Temperature -40°C ~ 70°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.469"$ (11.90mm)Contact Length - Post-Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Finish - Mating	-
Insulation Height $0.469" (11.90 \text{mm})$ Contact Length - Post - $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Finish Thickness - Mating	-
Contact Length - Post - $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Insulation Height	0.469" (11.90mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 70°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	-
Mated Stacking Heights	-
Ingress Protection	IP65/67 - Dust Tight, Water Resistant, Waterproof
Features	Board Guide
	Report errors?

09465004400 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

09465004400 Payment Methods



















09465004400 Shipping Methods













If you have any question about 09465004400, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com