

## 09677159615

### 09677159615 Information

Heisener.com	Part Number Manufacturer Category Description Package	09677159615 HARTING Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 15POS PNL MNT - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 09677159615 Specifications

Manufacturer Part Number99677159615ManufacturerHARTINGCategoryConnectors, InterconnectsPackage-Package-Series-Connector StyleD-Sub ConnectorConnector TypePug, Male PinsNumber of Positions15Number of Rows2Schall Size, Connector LayoutSignalContact TypeSignalMounting TypePanel MountFlauresSolder CupFlauresSolder CupShell Material, FinishSolder CupContact FinishGold or Gold-PalladiumContact Finish ThicknessJoin (0.76µm)Ingress Protection160 or Gold-PalladiumContact Finish ThicknessUL94 V-0Material Flammability RatingUL94 V-0		
CategoryConnectors, InterconnectsPackage-Series-Connector StyleD-Sub ConnectorsConnector TypeDesubNumber of Positions15Number of Rows2 (DA, A)Contact TypeSignalMounting TypeSolder CupFaturesSolder CupFaturesGrounding IndentsShell Material, FinishGold of Gold-PalladiumContact Finish ThicknessGold of Gold-PalladiumContact Finish ThicknessJuin (76µm)Shell Material, FinishSuper Conder Signal CupShell Material, FinishGold of Solder CupContact Finish ThicknessSuper Conder Signal CupContact Finish ThicknessSuper CupContact Finish ThicknessSuper CupShell Material Flammability RatingUL94 -0	Manufacturer Part Number	09677159615
D-Sub ConnectorsPackage-Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel MountFlange FeatureMating Side, Female Screwlock (M3)FeaturesSolder CupShell Material, FinishBrass, Tin PlatedContact Finish ThicknessGold or Gold-PalladiumIngress ProtectionIP67 - Dust Tight, WaterproofMetrial Flammability RatingUL94 V-0	Manufacturer	HARTING
Package-Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel MountFlange FeatureMating Side, Female Screwlock (M3)FeaturesSolder CupShell Material, FinishBrass, Tin PlatedContact Finish ThicknessGold or Gold-PalladiumIngress ProtectionMprotent Tight, WaterproofMaterial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeaturesGrounding IndentsShell Material, FinishGold or Gold-PalladiumContact FinishGold or Gold-PalladiumIngress ProtectionIP67 - Dust Tight, WaterproofMaterial Flanmability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeaturesGrounding IndentsShell Material, FinishGold or Gold-PalladiumContact Finish ThicknessSigni (D.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flanmability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeaturesSolder CupFeaturesGrounding IndentsShell Material, FinishGold or Gold-PalladiumContact Finish ThicknessSigni (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flanmability RatingUL94 V-0	Series	-
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel MountFlange FeatureMating Side, Female Screwlock (M3)TerminationSolder CupFeaturesGrounding IndentsShell Material, FinishBrass, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel MountFlange FeatureMating Side, Female Screwlock (M3)TerminationSolder CupFeaturesGrounding IndentsShell Material, FinishBrass, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel MountFlange FeatureMating Side, Female Screwlock (M3)TerminationSolder CupFeaturesGrounding IndentsShell Material, FinishBrass, Tin PlatedContact FinishGold or Gold-PalladiumContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypePanel MountFlange FeatureMating Side, Female Screwlock (M3)TerminationSolder CupFeaturesGrounding IndentsShell Material, FinishBrass, Tin PlatedContact FinishGold or Gold-PalladiumContact Finish Function30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (M3)TerminationSolder CupFeaturesGrounding IndentsShell Material, FinishBrass, Tin PlatedContact FinishGold or Gold-PalladiumContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureMating Side, Female Screwlock (M3)TerminationSolder CupFeaturesGrounding IndentsShell Material, FinishBrass, Tin PlatedContact FinishGold or Gold-PalladiumContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolder CupFeaturesGrounding IndentsShell Material, FinishBrass, Tin PlatedContact FinishGold or Gold-PalladiumContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Mounting Type	Panel Mount
FeaturesGrounding IndentsShell Material, FinishBrass, Tin PlatedContact FinishGold or Gold-PalladiumContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (M3)
Shell Material, FinishBrass, Tin PlatedContact FinishGold or Gold-PalladiumContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Termination	Solder Cup
Contact FinishGold or Gold-PalladiumContact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Features	Grounding Indents
Contact Finish Thickness30µin (0.76µm)Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Shell Material, Finish	Brass, Tin Plated
Ingress ProtectionIP67 - Dust Tight, WaterproofMaterial Flammability RatingUL94 V-0	Contact Finish	Gold or Gold-Palladium
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

### 09677159615 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# 09677159615 Payment MethodsImage: Image: Imag

If you have any question about 09677159615, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com