

0ATO015.HXGLO

0ATO015.HXGLO Information

	Heisener.com	Part Number Manufacturer Category Description Package	0ATO015.HXGLO Littelfuse Inc. Circuit Protection Fuses FUSE AUTO 15A 32VAC/VDC BLADE Blade, ATO/ATC For the pricing/inventory/lead time, please contact	
1	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0ATO015.HXGLO Specifications

ManufacturerLittlefuse Inc.CategoryCircuit ProtectionFusesFusesPackageBlade, ATO/ATCSeriesAt0?Fuse TypeAutomotiveCurrent Rating15AVoltage Rating - AC32VVoltage Rating - DCSalde, ATO/ATCResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlue		
CategoryCircuit ProtectionFusesPackageBlade, ATO/ATCSeriesATO?Fuse TypeAutonotiveCurrent Rating15AVoltage Rating - AC32VVoltage Rating - DCSalde, ATO/ATCResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension50°° L x 0.200° W x 0.480° H (19.05mm x 5.08mm x 12.19mm)	Manufacturer Part Number	0ATO015.HXGLO
FusesPackageBlade, ATO/ATCSeriesATO?Fuse TypeAutomotiveCurrent Rating15AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Manufacturer	Littelfuse Inc.
PackageBlade, ATO/ATCSeriesATO?Fuse TypeAutomotiveFuse TypeAutomotiveCurrent Rating15AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Category	Circuit Protection
Series ATO? Fuse Type Automotive Current Rating 15A Voltage Rating - AC 32V Voltage Rating - DC 32V Response Time Fast Package / Case Blade, ATO/ATC Mounting Type Holder Breaking Capacity @ Rated Voltage - Approvals CSA, SAE, UL Operating Temperature - Color Blue Size / Dimension 0.750" L x 0.200" W x 0.480" H (19.05mm x 12.19mm)		Fuses
Fuse TypeAutomotiveCurrent Rating15AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 12.19mm)	Package	Blade, ATO/ATC
Current Rating15ACurrent Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 12.19mm)	Series	ATO?
Voltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-Melting I2t-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Fuse Type	Automotive
Voltage Rating - DC32VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-Melting I2t-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Current Rating	15A
Response TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-Melting I2t-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Voltage Rating - AC	32V
Package / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage-Melting I2t-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Voltage Rating - DC	32V
Mounting TypeHolderBreaking Capacity @ Rated Voltage-Melting I2t-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Response Time	Fast
Breaking Capacity @ Rated Voltage-Melting I2t-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Package / Case	Blade, ATO/ATC
Melting I2t-ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Mounting Type	Holder
ApprovalsCSA, SAE, ULOperating Temperature-ColorBlueSize / Dimension0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Breaking Capacity @ Rated Voltage	-
Operating Temperature - Color Blue Size / Dimension 0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Melting I2t	-
Color Blue Size / Dimension 0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Approvals	CSA, SAE, UL
Size / Dimension 0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)	Operating Temperature	-
	Color	Blue
Report errors?	Size / Dimension	0.750" L x 0.200" W x 0.480" H (19.05mm x 5.08mm x 12.19mm)
		Report errors?

0ATO015.HXGLO Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0ATO015.HXGLO Payment Methods



0ATO015.HXGLO Shipping Methods



If you have any question about 0ATO015.HXGLO, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com