



OBLF009.T Information



For Reference Only

Part Number OBLF009.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 9A 250VAC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OBLF009.T Specifications

Manufacturer Part NumberOBLF009.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesBLFFuse TypeCartridgeCurrent Rating9AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)			
CategoryCircuit ProtectionBectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesBLFFuse TypeCartridgeCurrent Rating9AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0BLF009.T	
Package5AG, 10mm x 38.1mmSeriesBLFFuse TypeCartridgeCurrent Rating9AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.	
Package 5AG, 10mm x 38.1mm Series BLF Fuse Type Cartridge Current Rating 9A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection	
SeriesBLFFuse TypeCartridgeCurrent Rating9AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeCurrent Rating9AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	5AG, 10mm x 38.1mm	
Current Rating 9A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Series	BLF	
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V - 100 - 100 100 100 100 100 10	Fuse Type	Cartridge	
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Basel Age Fast Fast Fast Fast Fast Fast Fast Fast	Current Rating	9A	
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Electrical, Industrial - CSA, UR - ONE CSA, UR ONE CSA, UR - ONE CSA,	Voltage Rating - AC	250V	
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	-	
Features - Class - Approvals CSA, UR Operating Temperature - CSA, UR Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast	
Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Electrical, Industrial	
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-	
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-	
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CSA, UR	
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-	
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	10kA	
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder	
	Package / Case	5AG, 10mm x 38.1mm	
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)	
Report errors.			Report errors?

OBLF009.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0BLF009.T Payment Methods



















0BLF009.T Shipping Methods













If you have any question about 0BLF009.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com