



OBLF010.T Information



For Reference Only

Part Number 0BLF010.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 10A 250VAC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OBLF010.T Specifications

Manufacturer Part Number OBLF010.T Manufacturer Littelfuse Inc. Category Circuit Protection Bectrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series BLF Fuse Type Cartridge Current Rating 10A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series BLF Fuse Type Cartridge Current Rating 10A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0BLF010.T
Package 5AG, 10mm x 38.1mm Series BLF Fuse Type Cartridge Current Rating 10A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package 5AG, 10mm x 38.1mm Series BLF Fuse Type Cartridge Current Rating 10A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
SeriesBLFFuse TypeCartridgeCurrent Rating10AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 10A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 250V Cartridge 10A CSA, UR CSA, UR Foreith AB F	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 10A 250V 250V 250V 250V - CSA, UR - CRA 4 250V - CSA	Series	BLF
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 2600 - Response Time Fast Class - Class - Class - Approvals CSA, UR - Breaking Capacity @ Rated Voltage Holder 5AG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Response Time Fast Fast Fast Lectrical, Industrial - Lectrical	Current Rating	10A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Electrical, Industrial CSA, UR - Holder - Saga (10mm x 38.1mm) 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	-
Features - Class - CSA, UR Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CSA, UR
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

OBLF010.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0BLF010.T Payment Methods



















0BLF010.T Shipping Methods













If you have any question about 0BLF010.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com