



### **OBLN006.T Information**



For Reference Only

Part Number OBLN006.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 6A 250VAC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **0BLN006.T Specifications**

Manufacturer Part Number         OBLN006.T           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         BLN           Fuse Type         Cartridge           Current Rating         6A           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         CSA, PSE, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesBLNFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, PSE, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0BLN006.T
Package         5AG, 10mm x 38.1mm           Series         BLN           Fuse Type         Cartridge           Current Rating         6A           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         CSA, PSE, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package         5AG, 10mm x 38.1mm           Series         BLN           Fuse Type         Cartridge           Current Rating         6A           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         CSA, PSE, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
Series         BLN           Fuse Type         Cartridge           Current Rating         6A           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         CSA, PSE, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, PSE, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  6A 6A 6A 6A 6A 6A 6B 6A 6B	Series	BLN
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CSA, PSE, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  250V  250V  260V  26	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals CSA, PSE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  Fast  Fast Fast Fast Fast Fast Fast Fa	Current Rating	6A
Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals CSA, PSE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class - Approvals CSA, PSE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	-
Features - Class - CSA, PSE, UR  Approvals CSA, PSE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CSA, PSE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Electrical, Industrial
Approvals  CSA, PSE, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CSA, PSE, UR
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
· · · · · · · · · · · · · · · · · · ·	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

#### **OBLN006.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **0BLN006.T Payment Methods**



















## **0BLN006.T Shipping Methods**













If you have any question about 0BLN006.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com