



0CBO070.V Information

Part Number 0CBO070.V Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 70A 32VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0CBO070.V Specifications

Manufacturer Part NumberOCBO070.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CBOFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC-Voltage Rating - DC32VResponse TimeFastApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.812" Dia x 1.625" L (20.62mm x 41.28mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CBOFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC-Voltage Rating - DC32VResponse TimeFastApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Manufacturer Part Number	0CBO070.V
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? CBO Fuse Type Cartridge Current Rating 70A Voltage Rating - AC - Voltage Rating - DC 32V Response Time Fast Applications Lift Trucks Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CBOFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC-Voltage Rating - DC32VResponse TimeFastApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Category	Circuit Protection
SeriesPOWR-GARD? CBOFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC-Voltage Rating - DC32VResponse TimeFastApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.812" Dia x 1.625" L (20.62mm x 41.28mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating70AVoltage Rating - AC-Voltage Rating - DC32VResponse TimeFastApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Lift Trucks Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 70A 70A 70A 70A 70A 70A 70A 100A 10	Series	POWR-GARD? CBO
Voltage Rating - AC Voltage Rating - DC 32V Response Time Fast Applications Lift Trucks Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension - 0812" Dia x 1.625" L (20.62mm x 41.28mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Lift Trucks Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 32V 32V 32V 32V 844 845 845 845 845 845 846 846	Current Rating	70A
Response Time Applications Lift Trucks Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Lift Trucks - Breaking Capacity @ Capacity Bolt Mount	Voltage Rating - AC	-
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Lift Trucks - Lift Trucks - Cylindrical, Blade Terminal (Bolt) 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Voltage Rating - DC	32V
Features - Class - Class - Coperating Temperature - Coperating Capacity @ Rated Voltage 10kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Response Time	Fast
Class - Approvals - Class - Coperating Temperature - Streaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Applications	Lift Trucks
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension O.812" Dia x 1.625" L (20.62mm x 41.28mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.812" Dia x 1.625" L (20.62mm x 41.28mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.812" Dia x 1.625" L (20.62mm x 41.28mm)
		Report errors?

0CBO070.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0CBO070.V Payment Methods



















0CBO070.V Shipping Methods













If you have any question about 0CBO070.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com