



0CCK050.V Information

Heisener.com

Part Number 0CCK050.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 50A 125VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0CCK050.V	Specifications
-----------	-----------------------

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? CCK Fuse Type Cartridge Current Rating 50A Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Lift Trucks Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension OCCK050.V Littefuse Inc. Circuit Protection Electrical, Specialty Fuses Cartridge Cylindrical, Blade Terminal (Bolt) Size / Dimension Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CCKFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Manufacturer Part Number	0CCK050.V
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CCKFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CCKFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Category	Circuit Protection
SeriesPOWR-GARD? CCKFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Lift Trucks Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Siow 10kA Cylindrical, Blade Terminal (Bolt) Size / Dimension 50A 125V 125V 105V 106V 106V 10750" Dia x 3.629" L (19.05mm x 92.18mm)	Series	POWR-GARD? CCK
Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Lift Trucks Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Overating Temperature Solow - Overating Temperature Cylindrical, Blade Terminal (Bolt) Overating Temperature Overating Temperature Cylindrical, Blade Terminal (Bolt) Overating Temperature Cylindrical, Blade Terminal (Bolt) Overating Temperature Cylindrical, Blade Terminal (Bolt)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Lift Trucks Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 125V 125V 125V 106A 10750" Dia x 3.629" L (19.05mm x 92.18mm)	Current Rating	50A
Response Time Applications Lift Trucks Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Lift Trucks - Bolt Mount Class - Cylindrical, Blade Terminal (Bolt) O.750" Dia x 3.629" L (19.05mm x 92.18mm)	Voltage Rating - AC	-
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Lift Trucks Bolt Mount Cylindrical, Blade Terminal (Bolt) O.750" Dia x 3.629" L (19.05mm x 92.18mm)	Voltage Rating - DC	125V
Features - Class - Class - Coperating Temperature - Coperating Capacity @ Rated Voltage 10kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Response Time	Slow
Class - Approvals - Class - Coperating Temperature - Streaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Applications	Lift Trucks
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.750" Dia x 3.629" L (19.05mm x 92.18mm)
1		Report errors?

0CCK050.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0CCK050.V Payment Methods



















0CCK050.V Shipping Methods













If you have any question about 0CCK050.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com