

OFLA003.T Information

Heisener.com

Part Number 0FLA003.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 3A 125VAC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OFLA003.T Specifications

Manufacturer Part Number OFLA003.T Manufacturer Littelfuse Inc. Category Circuit Protection Package 5AG, 10mm x 38.1mm Series FLA Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 125V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	•	
Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series FLA Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 125V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Manufacturer Part Number	0FLA003.T
Blectrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series FLA Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 125V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Manufacturer	Littelfuse Inc.
Package5AG, 10mm x 38.1mmSeriesFLAFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC125VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mm	Category	Circuit Protection
Series FLA Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 125V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm		Electrical, Specialty Fuses
Fuse Type Current Rating 3A Voltage Rating - AC 125V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge Cartridge Sah AA AA AA AA AB AA AB AB AB AB AB AB AB	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 125V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case 3A 125V L UL L L L L L L L L L L L	Series	FLA
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case 125V 125V L L L L L L L L L L L L L	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case - Slow Lectrical, Industrial Lectri	Current Rating	3A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Slow Electrical, Industrial UL - Indicating - UL Stream of the package o	Voltage Rating - AC	125V
Applications Electrical, Industrial Features Indicating Class - Approvals UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Voltage Rating - DC	-
Features Indicating Class - Approvals UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Response Time	Slow
Class - Approvals UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case UL	Features	Indicating
Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Approvals	UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm	Breaking Capacity @ Rated Voltage	10kA
-	Mounting Type	Holder
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package / Case	5AG, 10mm x 38.1mm
2 2 2 (100 mm)	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
Report errors?		Report errors?

OFLA003.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0FLA003.T Payment Methods



















0FLA003.T Shipping Methods













If you have any question about 0FLA003.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com