



0FLM008.T Information



For Reference Only

Part Number0FLM008.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 8A 250VAC/125VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0FLM008.T Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series FLM Fuse Type Cartridge Current Rating 8A Voltage Rating - AC Voltage Rating - DC Response Time Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case 5AG, 10mm x 38.1mm Flum Flum Fund Fu		
CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesFLMFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSA, PSE, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0FLM008.T
Flectrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series FLM Fuse Type Cartridge Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package 5AG, 10mm x 38.1mm Series FLM Fuse Type Cartridge Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
Series FLM Fuse Type Cartridge Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating8AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSA, PSE, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8A Abarrow Sizo / Dimension Abarrow Abar	Series	FLM
Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 260V 108A Motor Protection CSA, PSE, QPL 40L 40L 40L 40L 40L 40L 40L 4	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 125V 125V 106A 106A 107 108A 1	Current Rating	8A
Response Time Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Slow Motor Protection - Hotor Protection - Slow Motor Protection - CSA, PSE, QPL, UL - 0,406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - AC	250V
Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	125V
Features - Class - Class - CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Slow
Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Motor Protection
Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CSA, PSE, QPL, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
1		Report errors?

0FLM008.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0FLM008.T Payment Methods


































If you have any question about 0FLM008.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com