

0FLM1.25T Information



For Reference Only

Part Number0FLM1.25TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 1.25A 250VAC/125VDC **Package** 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0FLM1.25T Specifications

Manufacturer Part Number OFLM1.25T Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series FLM Fuse Type Cartridge Current Rating 1.25A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
CategoryCircuit ProtectionPackage5AG, 10mm x 38.1mmSeriesFLMFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSA, PSE, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mm	Manufacturer Part Number	0FLM1.25T
Bectrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series FLM Fuse Type Cartridge Current Rating 1.25A Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Manufacturer	Littelfuse Inc.
Package5AG, 10mm x 38.1mmSeriesFLMFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSA, PSE, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mm	Category	Circuit Protection
SeriesFLMFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSA, PSE, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mm		Electrical, Specialty Fuses
Fuse Type Current Rating 1.25A Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge L25A L25A L25V Slow Motor Protection CSOA, PSE, QPL, UL CSA, PSE,	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Series	FLM
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case 250V 250V 125V Response Time Slow Motor Protection Features - CSA, PSE, QPL, UL Operating Temperature Found To MA Holder Holder SAG, 10mm x 38.1mm	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 125V 125V 125V 125V 125V 1064 1064 1064 1064 1066	Current Rating	1.25A
Response Time Slow Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Voltage Rating - AC	250V
Applications Motor Protection Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Voltage Rating - DC	125V
Features - Class - Common Comm	Response Time	Slow
Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Applications	Motor Protection
Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Approvals	CSA, PSE, QPL, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm	Breaking Capacity @ Rated Voltage	10kA
	Mounting Type	Holder
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package / Case	5AG, 10mm x 38.1mm
	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
Report errors?		Report errors?

0FLM1.25T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0FLM1.25T Payment Methods



















0FLM1.25T Shipping Methods













If you have any question about 0FLM1.25T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com