

0FLQ004.T

0FLQ004.T Information



Part Number	0FLQ004.T	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CARTRIDGE 4A 500VAC/300VDC	
Package	5AG, 10mm x 38.1mm	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0FLQ004.T Specifications

AnufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageSAG, 10mm x 38.1mmSeriesPOWR-GARD? FLQFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplications-Features-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmPackageSAG, 10mm x 38.1mmSeriesPOWR-GARD? FLQFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0FLQ004.T
ConstraintElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmPackagePOWR-GARD? FLQFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package5AG, 10mm x 38.1mmSeriesPOWR-GARD? FLQFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
NotePOWR-GARD? FLQFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting Type5AG, 10mm x 38.1nmPackage / Case0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating4ACurrent Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Series	POWR-GARD? FLQ
Voltage Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Fuse Type	Cartridge
Voltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Current Rating	4A
Response TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseSAG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - AC	500V
ApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeFolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	300V
InInFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Slow
Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Transformer Protection
ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CSA, UL
Mounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

0FLQ004.T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

OFLQ004.T Payment Methods Image: Im

If you have any question about 0FLQ004.T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com