

0FLQ04.5T Information



For Reference Only

Part Number 0FLQ04.5T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 4.5A 500VAC/300VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0FLQ04.5T Specifications

Manufacturer Part Number OFLQ04.5T Manufacturer Littelfuse Inc. Category Circuit Protection Beckage 5AG, 10mm x 38.1mm Series POWR-GARD? FLQ Fuse Type Cartridge Current Rating 4.5A Voltage Rating - AC 500V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? FLQFuse TypeCartridgeCurrent Rating4.5AVoltage Rating - AC500VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0FLQ04.5T
Flectrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? FLQ Fuse Type Cartridge Current Rating 4.5A Voltage Rating - AC 500V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package 5AG, 10mm x 38.1mm Series POWR-GARD? FLQ Fuse Type Cartridge Current Rating 4.5A Voltage Rating - AC 500V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
Series POWR-GARD? FLQ Fuse Type Cartridge Current Rating 4.5A Voltage Rating - AC 500V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 4.5A Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 4.5A A.A A.A A.A A.A A.A A.A A.A A.A A.A	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class - Approvals CysA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 4.5A 4.5A 4.5A 4.5A 4.5A 4.5A 4.5A 4.5	Series	POWR-GARD? FLQ
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 500V 300V 300V CRA Slow ARESPONSE CRA Slow Cransformer Protection - CRA - CSA, UL CSA, UL CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Holder For Case SAG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Transformer Protection Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V Slow Slow Cransformer Protection - CRA - CSA, UL CSA, UL Operating Temperature - SAG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Current Rating	4.5A
Response Time Applications Transformer Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Slow Transformer Protection - CSA, UL - CSA, UL - Breaking Capacity @ Rated Voltage Holder Holder 5AG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - AC	500V
Applications Transformer Protection Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	300V
Features - Class - CSA, UL Operating Temperature - CSA, UL Operating Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Slow
Class - CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Transformer Protection
Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

0FLQ04.5T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0FLQ04.5T Payment Methods



















0FLQ04.5T Shipping Methods













If you have any question about 0FLQ04.5T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com