

0JLS040.T

0JLS040.T Information



Part Number	0JLS040.T	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CRTRDGE 40A 600VAC NON STD	
Package	Cartridge, Non-Standard	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0JLS040.T Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardPackagePOWR-GARD? JLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature200KAMonting TypeHolderPackage / CaseCartridge, Non-Standard		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Manufacturer Part Number	0JLS040.T
BitElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Type-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature200KABreaking Capacity @ Rated Voltage200KAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.663" Dia x 2.374" L (27.00mm x 60.30mm)	Package	Cartridge, Non-Standard
Current Rating40ACurrent Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Series	POWR-GARD? JLS
Voltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Current Rating	40A
Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Voltage Rating - AC	600V
ApplicationsElectrical, IndustrialApplications-Features-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Voltage Rating - DC	-
Features-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Response Time	Fast
ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Class	J
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Approvals	CE, CSA, QPL, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.063" Dia x 2.374" L (27.00mm x 60.30mm)
		Report errors?

0JLS040.T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0JLS040.T Payment Methods



0JLS040.T Shipping Methods



If you have any question about 0JLS040.T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com