



0JLS045.T Information

Heisener.com

For Reference Only

Part Number OJLS045.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 45A 600VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0JLS045.T Specifications

Manufacturer Part NumberOJLS045.TManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Manufacturer Part Number	OJLS045.T
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLSFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class J Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 45A 600V 6	Series	POWR-GARD? JLS
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class J Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class J Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cartridge, Non-Standard Size / Dimension - Size / Dimension - Cartridge, Non-Standard Siz	Current Rating	45A
Response Time Applications Electrical, Industrial Features - Class J Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial - CE, CSA, QPL Holder - CE, CSA, QPL, UL - CE, CSA, QPL, U	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class J Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Voltage Rating - DC	-
Features - Class J Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Response Time	Fast
Class Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension J CE, CSA, QPL, UL Cartridge, Voltage Cartridge, Voltage 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Class	J
Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.063" Dia x 2.374" L (27.00mm x 60.30mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.063" Dia x 2.374" L (27.00mm x 60.30mm)
		Report errors?

0JLS045.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0JLS045.T Payment Methods



















0JLS045.T Shipping Methods













If you have any question about 0JLS045.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com