



0JTD03.5T Information

Can Heisener.com

Part Number 0JTD03.5T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 3.5A 600VAC/300VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0JTD03.5T Specifications

Manufacturer Part Number OITD03.5T Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD?, POWR-PRO? JTD Fuse Type Cartridge Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.252" L (20.60mm x 57.20mm) Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD?, POWR-PRO? JTD Fuse Type Cartridge Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses POWR-GARD?, POWR-PRO? JTD TD Electrical, Specialty Fuses Fowns-Standard Electrical, Specialty Fuses Electrical Fuses	Manufacturer Part Number	0JTD03.5T
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD?, POWR-PRO? JTD Fuse Type Cartridge Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? JTDFuse TypeCartridgeCurrent Rating3.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? JTDFuse TypeCartridgeCurrent Rating3.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.252" L (20.60mm x 57.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating3.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 3.5A 3.5A 3.5A 400V 600V 300V Transformer Protection Cransformer Protection - Capacity - CE, CSA, UL - CE, CSA,	Series	POWR-GARD?, POWR-PRO? JTD
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Transformer Protection Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V Approvals CE, CSA CE, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COPIET Temperature COPIET	Current Rating	3.5A
Response Time Applications Transformer Protection Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Transformer Protection - CRACH Protection - CE, CSA, UL -	Voltage Rating - AC	600V
Applications Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Transformer Protection Transformer Protection Transformer Protection Holder CE, CSA, UL COE, CSA, UL Holder CE, CSA, UL CARTRIDIAN AC, 20kA DC Holder Holder ORANGE (Case Cartridge, Non-Standard ORANGE (Case Cartridge, Non-Standard ORANGE (CASE CASE) ORANGE (CASE CASE CASE CASE CASE CASE CASE CASE	Voltage Rating - DC	300V
Features - Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Response Time	Slow
Class Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension J CE, CSA, UL - Cartridge, Voltage Custoff Color Cartridge, Non-Standard Output Dia x 2.252" L (20.60mm x 57.20mm)	Applications	Transformer Protection
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Class	J
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 2.252" L (20.60mm x 57.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 2.252" L (20.60mm x 57.20mm)
		Report errors?

0JTD03.5T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0JTD03.5T Payment Methods



















0JTD03.5T Shipping Methods













If you have any question about 0JTD03.5T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com