



0JTD110.XXID Information

Heisener.com

Part Number 0JTD110.XXID

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionFUSE CRTRDGE 110A 600VAC/500VDC**Package**Cylindrical, Alarm Indicator, Blade Terminal

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0JTD110.XXID Specifications

Manufacturer Part NumberOITD110.XXIDManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Alarm Indicator, Blade TerminalSeriesPOWR-GARD?, POWR-PRO? ITD_IDFuse TypeCartridgeCurrent Rating110AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Alarm Indicator, Blade TerminalSeriesPOWR-GARD?, POWR-PRO? JTD_IDFuse TypeCartridgeCurrent Rating110AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Manufacturer Part Number	0JTD110.XXID
Electrical, Specialty Fuses Package Cylindrical, Alarm Indicator, Blade Terminal Series POWR-GARD?, POWR-PRO? JTD_ID Fuse Type Cartridge Current Rating 110A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Slow Applications Transformer Protection Features Indicating Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Manufacturer	Littelfuse Inc.
Package Cylindrical, Alarm Indicator, Blade Terminal Series POWR-GARD?, POWR-PRO? JTD_ID Fuse Type Cartridge Current Rating 110A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Slow Applications Transformer Protection Features Indicating Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Category	Circuit Protection
Series POWR-GARD?, POWR-PRO? JTD_ID Fuse Type Cartridge Current Rating 110A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Slow Applications Transformer Protection Features Indicating Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating110AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Package	Cylindrical, Alarm Indicator, Blade Terminal
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Slow Applications Transformer Protection Features Indicating Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Sind Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 110A 600V 6	Series	POWR-GARD?, POWR-PRO? JTD_ID
Voltage Rating - AC Voltage Rating - DC 500V Response Time Slow Applications Transformer Protection Features Indicating Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Transformer Protection Features Indicating Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 500V Slow CR Slow Cransformer Protection Transformer Protection Cransformer Protection Transformer Protection Cransformer Protection Transformer Protection Transformer Protection 1ndicating 200kA AC, 20kA DC Holder Cylindrical, Alarm Indicator, Blade Terminal 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Current Rating	110A
Response Time Applications Transformer Protection Features Indicating Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension Slow Transformer Protection Transformer Protection CE, CSA, UL CE, CS	Voltage Rating - AC	600V
Applications Features Indicating Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension Transformer Protection Indicating Fromperature J U U U U U U U U U U U U U U U U U U	Voltage Rating - DC	500V
Features Indicating Class J Approvals CE, CSA, UL Operating TemperatureBreaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension Indicating J CE, CSA, UL	Response Time	Slow
Class Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension J CE, CSA, UL	Applications	Transformer Protection
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Class	J
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Operating Temperature	-
Package / Case Cylindrical, Alarm Indicator, Blade Terminal Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Alarm Indicator, Blade Terminal
Report errors?	Size / Dimension	1.500" Dia x 3.000" L (38.10mm x 76.20mm)
		Report errors?

0JTD110.XXID Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0JTD110.XXID Payment Methods



















0JTD110.XXID Shipping Methods













If you have any question about 0JTD110.XXID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com