

0JTD350.X

0JTD350.X Information

	Part Number	0JTD350.X
Heisener. C	Manufacturer	Littelfuse Inc.
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	FUSE CRTRDGE 350A 600VAC/500VDC
	Package	Cylindrical, Blade Terminals
		For the pricing/inventory/lead time, please contact
For Reference	ee Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0JTD350.X Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? JTDFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC600VVoltage Rating - DCSlowApplicationsSlowFeaturesSlowClarsJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200k AC, 20k A DCManufa TypeHolderPackage / CaseSuow TerminalsSize / Dimension2000" Dia x 3.374" L (50.80mm x 85.70mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsPackagePOWR-GARD?, POWR-PRO? JTDSteriesPOWR-GARD?, POWR-PRO? JTDFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseSu00" Dia x 3.374" L (50.80mm x 85.70mm)	Manufacturer Part Number	0JTD350.X
Current RatingElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? JTDFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2,000" Dia x 3.374" L (50.80mm x 85.70mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? JTDFuse TypeCartridgeCurrent RatingStoAVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? JTDFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating350AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200KA AC, 20KA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Package	Cylindrical, Blade Terminals
Current Rating350ACurrent Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Series	POWR-GARD?, POWR-PRO? JTD
Voltage Rating - AC600VVoltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case2,000" Dia x 3,374" L (50.80mm x 85.70mm)	Fuse Type	Cartridge
Voltage Rating - DC500VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Current Rating	350A
Response TimeSlowApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Voltage Rating - AC	600V
ApplicationsTransformer ProtectionFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Voltage Rating - DC	500V
InInFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Response Time	Slow
ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Applications	Transformer Protection
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Class	J
Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Operating Temperature	-
Package / CaseCylindrical, Blade TerminalsSize / Dimension2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 2.000" Dia x 3.374" L (50.80mm x 85.70mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	2.000" Dia x 3.374" L (50.80mm x 85.70mm)
		Report errors?

0JTD350.X Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0JTD350.X Payment Methods



0JTD350.X Shipping Methods



If you have any question about 0JTD350.X, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com