

0KLC17.5T

0KLC17.5T Information

	Heisener.com	Part Number	0KLC17.5T
		Manufacturer	Littelfuse Inc.
		Category	Circuit Protection Electrical, Specialty Fuses
		Description	FUSE CARTRIDGE 17.5A 600VAC CYL
		Package	Cylindrical, Blade Terminal (Bolt)
			For the pricing/inventory/lead time, please contact
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0KLC17.5T Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? KLCFuse TypeCatridgeCurrent RatingACVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200k AC, 20kA DCPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension563" Dia x 1.874" L (14.30mm x 47.60mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? KLCFuse TypeCartridgeCurrent Rating17.5AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature200KA AC, 20kA DCBreaking Capacity @ Rated VoltageSolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Manufacturer Part Number	0KLC17.5T
DefinitionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? KLCFuse TypeCartridgeCurrent Rating17.5AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension5.63" Dia x 1.874" L (14.30mm x 47.60mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? KLCFuse TypeCartridgeCurrent Rating17.5AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLCFuse TypeCartridgeCurrent Rating17.5AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating TypeSolt AC2, 20kA DCBreaking Capacity @ Rated Voltage200kA AC2, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating17.5AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating17.5ACurrent Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Series	POWR-GARD? KLC
Voltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Current Rating	17.5A
Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Voltage Rating - AC	600V
ApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Voltage Rating - DC	-
Fratures-Features-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Response Time	Fast
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Applications	Semiconductors
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Class	-
Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Operating Temperature	-
Package / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.563" Dia x 1.874" L (14.30mm x 47.60mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.563" Dia x 1.874" L (14.30mm x 47.60mm)
		Report errors?

0KLC17.5T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or

replacement, but the items must be returned in their original condition.



Service Guarantees We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0KLC17.5T Payment Methods



0KLC17.5T Shipping Methods



If you have any question about 0KLC17.5T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com